

PEINTURE BLANCHE - 633507

**SAFETY DATA SHEET**

( REACH regulation (EC) n° 1907/2006 - n° 2015/830)

**SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**

**1.1 . Product identifier**

Product name : PEINTURE BLANCHE  
Product code : 633507

**1.2 . Relevant identified uses of the substance or mixture and uses advised against**

**1.3 . Details of the supplier of the safety data sheet**

Registered name company : IPH BRANDS  
Address : 31 rue de la Baume, 75008 Paris, France  
Telephone : +33 1-44-86-08-10  
infoclient@giss.fr  
http://www.giss.fr

**1.4 . Emergency telephone number : +33 (0)1 45 42 59 59.**

Association/Organisation : INRS / ORFILA <http://www.centres-antipoison.net>.

**SECTION 2 : HAZARDS IDENTIFICATION**

**2.1 . Classification of the substance or mixture**

**In compliance with EC regulation No. 1272/2008 and its amendments.**

Aerosol, Category 1 (Aerosol 1, H222 - H229).  
Repeated exposure may cause skin dryness or cracking (EUH066).  
Eye irritation, Category 2 (Eye Irrit. 2, H319).  
Specific target organ toxicity (single exposure), Category 3 (STOT SE 3, H336).  
Hazardous to the aquatic environment - Chronic hazard, Category 3 (Aquatic Chronic 3, H412).

**2.2 . Label elements**

Mixture for aerosol application.

**In compliance with EC regulation No. 1272/2008 and its amendments.**

Hazard pictograms :



GHS07



GHS02

Signal Word :

DANGER

Product identifiers :

607-025-00-1 N- BUTYL ACETATE

Hazard statements :

H222

Extremely flammable aerosol.

H229

Pressurised container: May burst if heated.

H319

Causes serious eye irritation.

H336

May cause drowsiness or dizziness.

H412

Harmful to aquatic life with long lasting effects.

EUH066

Repeated exposure may cause skin dryness or cracking.

Precautionary statements - General :

P101

If medical advice is needed, have product container or label at hand.

P102

Keep out of reach of children.

Precautionary statements - Prevention :

**PEINTURE BLANCHE - 633507**

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211 Do not spray on an open flame or other ignition source.
- P251 Do not pierce or burn, even after use.
- P271 Use only outdoors or in a well-ventilated area.
- Precautionary statements - Storage :  
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 oC/122oF.
- Precautionary statements - Disposal :  
P501 Eliminate the contents / container according to the local regulations.

**2.3 . Other hazards**

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC)  $\geq 0.1\%$  published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

**SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS**

**3.2 . Mixtures**

**Composition :**

Identification	(EC) 1272/2008	Note	%
INDEX: 601_004_00_0 CAS: 106-97-8 EC: 203-448-7 REACH: 01-2119474691-32  BUTANE	GHS02, GHS04 Dgr Flam. Gas 1, H220 Press. Gas, H280	C [1] [7]	25 $\leq$ x % < 50
INDEX: 603_019_00_8 CAS: 115-10-6 EC: 204-065-8 REACH: 01-2119472128-37  DIMETHYL ETHER	GHS02 Dgr Flam. Gas 1, H220 Press. Gas, H280	[1] [7]	10 $\leq$ x % < 25
INDEX: 607-025-00-1 CAS: 123-86-4 EC: 204-658-1 REACH: 01-2119485493-29  N- BUTYL ACETATE	GHS02, GHS07 Wng Flam. Liq. 3, H226 STOT SE 3, H336 EUH:066	[1]	10 $\leq$ x % < 25
INDEX: 603-117-00-0 CAS: 67-63-0 EC: 200-661-7 REACH: 01-2119457558-25  PROPAN-2-OL	GHS02, GHS07 Dgr Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	[1]	10 $\leq$ x % < 25
INDEX: 607-022-00-5 CAS: 141-78-6 EC: 205-500-4 REACH: 01-2119475103-46  ETHYL ACETATE	GHS02, GHS07 Dgr Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH:066	[1]	10 $\leq$ x % < 25

**PEINTURE BLANCHE - 633507**

INDEX: 000000000130 SOLVANT NAPHTHA AROMATIQUE LEGER MOINS DE 0.1% BENZENE	GHS09, GHS07, GHS08, GHS02 Dgr Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H335 STOT SE 3, H336 Aquatic Chronic 2, H411 EUH:066		2.5 <= x % < 10
INDEX: 649-328-00-1 CAS: 64742-49-0 EC: 265-151-9  NAPHTHA (PETROLEUM), HYDROTREATED LIGHT	GHS08 Dgr Asp. Tox. 1, H304	P	2.5 <= x % < 10
INDEX: A13463677 CAS: 13463-67-7 EC: 236-675-5 REACH: 01-2119489379-17  DIOXYDE DE TITANE		[1]	1 <= x % < 2.5
INDEX: A64742945 CAS: 64742-94-5 EC: 265-198-5  SOLVENT NAPHTHA (PETROLEUM), HEAVY AROM.	GHS09, GHS07, GHS08 Dgr Asp. Tox. 1, H304 STOT SE 3, H336 Aquatic Chronic 2, H411 EUH:066		1 <= x % < 2.5

**Information on ingredients :**

[7] Propellant gas

[1] Substance for which maximum workplace exposure limits are available.

Note P: The carcinogen or mutagen classification does not apply because the substance contains less than 0.1 % w/w of benzene (EINECS 200-753-7).

**SECTION 4 : FIRST AID MEASURES**

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

**4.1 . Description of first aid measures**

**In the event of exposure by inhalation :**

In the event of massive inhalation, remove the person exposed to fresh air. Keep warm and at rest.

If the person is unconscious, place in recovery position. Notify a doctor in all events, to ascertain whether observation and supportive hospital care will be necessary.

If breathing is irregular or has stopped, effect mouth-to-mouth resuscitation and call a doctor.

**In the event of splashes or contact with eyes :**

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

If there is any redness, pain or visual impairment, consult an ophthalmologist.

**In the event of splashes or contact with skin :**

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

**In the event of swallowing :**

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention, showing the label.

**PEINTURE BLANCHE - 633507**

---

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

**4.2 . Most important symptoms and effects, both acute and delayed**

No data available.

**4.3 . Indication of any immediate medical attention and special treatment needed**

No data available.

**PEINTURE BLANCHE - CTG153020/0/03**

---

**SECTION 5 : FIREFIGHTING MEASURES**

Flammable.

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

**5.1 . Extinguishing media**

Keep packages near the fire cool, to prevent pressurised containers from bursting.

**Suitable methods of extinction**

In the event of a fire, use :

- sprayed water or water mist
- water with AFFF (Aqueous Film Forming Foam) additive

Prevent the effluent of fire-fighting measures from entering drains or waterways.

**Unsuitable methods of extinction**

In the event of a fire, do not use :

- water jet

**5.2 . Special hazards arising from the substance or mixture**

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO )
- carbon dioxide (CO 2)

**5.3 . Advice for firefighters**

Due to the toxicity of the gas emitted on thermal decomposition of the products, fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

---

**SECTION 6 : ACCIDENTAL RELEASE MEASURES**

**6.1. Personal precautions, protective equipment and emergency procedures** Consult the safety measures listed under headings 7 and 8.

**For non first aid worker**

Because of the organic solvents contained in the mixture, eliminate sources of ignition and ventilate the area.

Avoid inhaling the vapors.

Avoid any contact with the skin and eyes.

If a large quantity has been spilt, evacuate all personnel and only allow intervention by trained operators equipped with safety apparatus.

**For first aid worker**

First aid workers will be equipped with suitable personal protective equipment (See section 8).

**6.2. Environmental precautions**

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

If the product contaminates waterways, rivers or drains, alert the relevant authorities in accordance with statutory procedures

Use drums to dispose of collected waste in compliance with current regulations (see section 13).

**6.3. Methods and material for containment and cleaning up**

Clean preferably with a detergent, do not use solvents.

Use some absorbent.

The elimination must be carried out by a registered salvage professional.

**6.4. Reference to other sections** No data available.

## **SECTION 7 : HANDLING AND STORAGE**

Requirements relating to storage premises apply to all facilities where the mixture is handled.

### **7.1 . Precautions for safe handling**

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

Remove contaminated clothing and protective equipment before entering eating areas.

### **Fire prevention :**

Handle in well-ventilated areas.

Vapours are heavier than air. They can spread along the ground and form mixtures that are explosive with air.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Do not spray on a naked flame or any incandescent material.

Do not pierce or burn, even after use.

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

### **Recommended equipment and procedures :**

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Do not breathe in aerosols.

Avoid inhaling vapors. Carry out any industrial operation which may give rise to this in a sealed apparatus.

Provide vapor extraction at the emission source and also general ventilation of the premises.

Also provide breathing apparatus for certain short tasks of an exceptional nature and for emergency interventions.

In all cases, recover emissions at source.

Avoid skin and eye contact with this mixture.

Packages which have been opened must be reclosed carefully and stored in an upright position.

### **Prohibited equipment and procedures :**

No smoking, eating or drinking in areas where the mixture is used.

Never open the packages under pressure.

### **7.2 . Conditions for safe storage, including any incompatibilities**

No data available.

### **Storage**

Keep out of reach of children.

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C.

### **Packaging**

**PEINTURE BLANCHE - CTG153020/0/03**

Always keep in packaging made of an identical material to the original.

**7.3 . Specific end use(s )**

No data available.

**SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1 . Control parameters**

**Occupational exposure limits :**

- European Union (2017/164/UE, 2009/161/UE, 2006/15/CE, 2000/39/CE, 98/24/CE )

- France (INRS - ED984 :2012) :

CAS	VME-ppm :	VME-mg/m3 :	VLE-ppm :	VLE-mg/m3 :	Notes :	TMP No :
106-97-8	800	1900	-	-	-	-
115-10-6	1000	1920	-	-	-	-
123-86-4	150	710	200	940	-	84
67-63-0	-	-	400	980	-	84
141-78-6	400	1400	-	-	-	84
13463-67-7	-	10	-	-	-	-

- UK / WEL (Workplace exposure limits, EH40/2005, 2007) :

CAS	VME-mg/m3 :	VME-ppm :	VLE-mg/m3 :	VLE-ppm :	Notes :
115-10-6	1920	1000	-	-	-
141-78-6	734	200	1468	400	-
CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
106-97-8	600 ppm 1450 mg/m3	750 ppm 1810 mg/m 3		Carc	
115-10-6	400 ppm 766 mg/m3	500 ppm 958 mg/m 3			
123-86-4	150 ppm 724 mg/m3	200 ppm 966 mg/m 3			
67-63-0	400 ppm 999 mg/m3	500 ppm 1250 mg/m 3			
141-78-6	200 ppm	400 ppm			
13463-67-7	10 mg/m 3				

**8.2 . Exposure controls**

**Personal protection measures, such as personal protective equipment**

Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- **Eye / face protection** Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166.

In the event of high danger, protect the face with a face shield.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

**PEINTURE BLANCHE - CTG153020/0/03**

---

**- Hand protection**

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required. Type of gloves recommended :

- PVA (Polyvinyl alcohol )
- Butyl Rubber (Isobutylene-isoprene copolymer )



**PEINTURE BLANCHE - CTG153020/0/03**

---

Recommended properties :

- Impervious gloves in accordance with standard EN 374

**- Body protection**

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing :

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034 to prevent skin contact.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

**- Respiratory protection**

Avoid breathing vapours.

If the ventilation is insufficient, wear appropriate breathing apparatus.

When workers are confronted with concentrations that are above occupational exposure limits, they must wear a suitable, approved, respiratory protection device.

Type of FFP mask :

Wear a disposable half-mask aerosol filter in accordance with standard EN149.

Category : - FFP 1

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387 :

- A1 (Brown )

Particle filter according to standard EN143 :

- P1 (White )

---

**SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES**

**9.1. Information on basic physical and chemical properties**

**General information :**

Physical state : Fluid liquid.  
Spray.

**Important health, safety and environmental information**

pH :	Not relevant.
Boiling point/boiling range :	Not specified.
Vapour pressure (50°C) :	Below 110 kPa (1.10 bar).
Density :	> 1
Water solubility :	Insoluble.
Melting point/melting range :	Not specified.
Self-ignition temperature :	Not specified.
Decomposition point/decomposition range :	Not specified.
Chemical combustion heat :	>= 30 kJ/g.

**9.2. Other**

**information** No data available.

---

**SECTION 10 : STABILITY AND REACTIVITY**

**10.1. Reactivity** No data available.

**10.2. Chemical stability**

This mixture is stable under the recommended handling and storage conditions in section 7.

**10.3. Possibility of hazardous reactions**

**PEINTURE BLANCHE - CTG153020/0/03**

---

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

**10.4. Conditions to avoid**

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises. Avoid :

- heating
- heat
- accumulation of electrostatic charges.
- flames and hot surfaces

**10.5 . Incompatible materials**

Keep away from :

- strong acids
- strong oxidising agents

**10.6 . Hazardous decomposition products** The

thermal decomposition may release/form :

- carbon monoxide (CO )
- carbon dioxide (CO 2)

---

**SECTION 11 : TOXICOLOGICAL INFORMATION**

**11.1 . Information on toxicological effects**

Exposure to vapours from solvents in the mixture in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.

Symptoms produced will include headaches, numbness, dizziness, fatigue, muscular asthenia and, in extreme cases, loss of consciousness.

Repeated or prolonged contact with the mixture may cause removal of natural oil from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

May have reversible effects on the eyes, such as eye irritation which is totally reversible by the end of observation at 21 days.

Splashes in the eyes may cause irritation and reversible damage

Narcotic effects may occur, such as drowsiness, narcosis, decreased alertness, loss of reflexes, lack of coordination or dizziness.

Effects may also occur in the form of violent headaches or nausea, judgement disorder, giddiness, irritability, fatigue or memory disturbance.

**11.1.1 . Substances**

No toxicological data available for the substances.

**11.1.2 . Mixture**

No toxicological data available for the mixture.

**Monograph(s) from the IARC (International Agency for Research on Cancer) :**

CAS 67-63-0 : IARC Group 3 : The agent is not classifiable as to its carcinogenicity to humans.

---

**SECTION 12 : ECOLOGICAL INFORMATION**

Harmful to aquatic life with long lasting effects.

The product must not be allowed to run into drains or waterways.

**12.1 . Toxicity**

**12.1.2 . Mixtures**

No aquatic toxicity data available for the mixture.

**12.2 . Persistence and degradability**

No data available.

**12.3 . Bioaccumulative potential**

No data available.

**12 .4 . Mobility in soil**

No data available.

**PEINTURE BLANCHE - CTG153020/0/03**

**12.5 . Results of PBT and vPvB assessment**

No data available.

**12.6 . Other adverse effects**

**SECTION 13 : DISPOSAL CONSIDERATIONS**

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

**13.1 . Waste treatment methods**

Do not pour into drains or waterways.

**Waste :**

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.  
 Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

**Soiled packaging :**

Empty container completely. Keep label(s) on container.  
 Give to a certified disposal contractor.

**SECTION 14 : TRANSPORT INFORMATION**

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2015 - IMDG 2014 - ICAO/IATA 2015).

**14.1 . UN number**

1950

**14.2 . UN proper shipping name**

UN1950=AEROSOLS, flammable

**14.3 . Transport hazard class(es )**

- Classification :



2.1

**14.4 . Packing group**

-

**14.5 . Environmental hazards**

-

**14.6. Special precautions for user**

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	2	5F	-	2.1	-	1 L	190 327 344 625	E0	2	D
IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ			
	2.1	See SP63	-	SP277	F-D,S-U	63 190 277 327 344 959	E0			
IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ	
	2.1	-	-	203	75 kg	203	150 kg	A145 A167 A802	E0	
	2.1	-	-	Y203	30 kg G	-	-	A145 A167 A802	E0	

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

No data available.

---

## SECTION 15 : REGULATORY INFORMATION

### 15.1 . Safety, health and environmental regulations/legislation specific for the substance or mixture

#### - Classification and labelling information included in section 2:

The following regulations have been used:

- Directive 75/324/CEE modified by directive 2013/10/UE
- EU Regulation No. 1272/2008 amended by EU Regulation No. 487/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 758/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 944/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 605/2014.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 1297/2014.

- **Container information** : No data available.

- **Particular provisions** : No data available.

### 15.2 . Chemical safety assessment

No data available.

---

## SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

### Wording of the phrases mentioned in section 3 :

H220	Extremely flammable gas.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

### Abbreviations :

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefährdungsklasse (Water Hazard Class).

GHS02 : Flame

GHS07 : Exclamation mark

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.