# SAFETY DATA SHEET

Based upon Regulation (EC) No 1907/2006, as amended by Regulation (EU) No 2015/830

# **GISS MOUSSE PU [610342]**

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name **Registration number REACH** Product type REACH

: GISS MOUSSE PU [610342] : Not applicable (mixture)

: Mixture

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant identified uses polyurethane

1.2.2 Uses advised against No uses advised against known

#### 1.3. Details of the supplier of the safety data sheet

**Rubix Engineering** 

31, Rue de la Baume 75008 PARIS, France

Tel: +33 (0)1.44.86.08.10

infoclient@giss.fr

#### 1.4. Emergency telephone number

24h/24h (Telephone advice: English, French, German, Dutch):

+32 14 58 45 45 (BIG)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Classified as dange	erous according to	o the criteria of Regulation (EC) No 1272/2008
Class	Category	Hazard statements
Aerosol	category 1	H222: Extremely flammable aerosol.
Aerosol	category 1	H229: Pressurised container: May burst if heated.
Carc.	category 2	H351: Suspected of causing cancer.
Lact.	-	H362: May cause harm to breast-fed children.
Resp. Sens.	category 1	H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin Sens.	category 1	H317: May cause an allergic skin reaction.
Acute Tox.	category 4	H332: Harmful if inhaled.
STOT RE	category 2	H373: May cause damage to organs through prolonged or repeated exposure if inhaled.
Skin Irrit.	category 2	H315: Causes skin irritation.
Eye Irrit.	category 2	H319: Causes serious eye irritation.
STOT SE	category 3	H335: May cause respiratory irritation.
Aquatic Chronic	category 4	H413: May cause long lasting harmful effects to aquatic life.

#### 2.2. Label elements



Contains: alkanes, C14-17, chloro; polymethylene polyphenyl isocyanate. Signal word Danger H-statements

H229 Pressurised container: May burst if heated.	H222	Extremely flammable aerosol.
	H229	Pressurised container: May burst if heated.

Created by: Brandweerinformatiecentrum voor gevaarlijke stoffen vzw (BIG) Technische Schoolstraat 43 A, B-2440 Geel http://www.big.be © BIG vzw Reason for revision: 2.2

Revision number: 0003

Product number: 58439

Publication date: 2017-06-02

Date of revision: 2017-12-17

134-15960-598-en

H351	Suspected of causing cancer.
H362	May cause harm to breast-fed children.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317	May cause an allergic skin reaction.
H332	Harmful if inhaled.
H373	May cause damage to organs through prolonged or repeated exposure if inhaled.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H413	May cause long lasting harmful effects to aquatic life.
P-statements	
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P308 + P313	IF exposed or concerned: Get medical advice/attention.
P405	Store locked up.
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122°F.
P501	Dispose of contents/container in accordance with local/regional/national/international regulation.
Supplemental information	
	- Persons already sensitised to diisocyanates may develop allergic reactions when using this product.
	- Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.

- This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

#### 2.3. Other hazards

Gas/vapour spreads at floor level: ignition hazard

### SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name REACH Registration No	CAS No EC No	Conc. (C)	Classification according to CLP	Note	Remark
propane 01-2119486944-21	74-98-6 200-827-9	C>1%	Flam. Gas 1; H220 Press. Gas - Liquefied gas;	(1)(2)(10)	Propellant
dimethyl ether 01-2119472128-37	115-10-6 204-065-8	C>1%	Flam. Gas 1; H220 Press. Gas - Liquefied gas;	(1)(2)(10)	Propellant
isobutane 01-2119485395-27	75-28-5 200-857-2	C>1%	Flam. Gas 1; H220 Press. Gas - Liquefied gas;	(1)(2)(10)	Propellant
(1,3-butadiene, conc<0.1%)					
alkanes, C14-17, chloro 01-2119519269-33	85535-85-9 287-477-0	1% <c<20%< td=""><td>Lact. ; H362 Aquatic Acute 1; H400 Aquatic Chronic 1; H410</td><td>(1)(2)(8)(10)</td><td>Constituent</td></c<20%<>	Lact. ; H362 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	(1)(2)(8)(10)	Constituent
polymethylene polyphenyl isocyanate	9016-87-9	C>25 %	Carc. 2; H351 Resp. Sens. 1; H334 Skin Sens. 1; H317 Acute Tox. 4; H332 STOT RE 2; H373 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335	(1)(2)(8)(10)(18)	Constituent

(1) For H-statements in full: see heading 16

(2) Substance with a Community workplace exposure limit

(8) Specific concentration limits, see heading 16

(10) Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006

(18) Polymethylene polyphenyl isocyanate, contains > 0.1% MDI-isomers

Reason for revision: 2.2

Revision number: 0003

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

#### General:

GENERAL. Check the vital functions. Unconscious: maintain adequate airway and respiration. Respiratory arrest: artificial respiration or oxygen. Cardiac arrest: perform resuscitation. Victim conscious with laboured breathing: half-seated. Victim in shock: on his back with legs slightly raised. Vomiting: prevent asphyxia/aspiration pneumonia. Prevent cooling by covering the victim (no warming up). Keep watching the victim. Give psychological aid. Keep the victim calm, avoid physical strain. Depending on the victim's condition: doctor/hospital.

#### After inhalation:

Remove the victim into fresh air. Respiratory problems: consult a doctor/medical service.

#### After skin contact:

Wash immediately with lots of water. Take victim to a doctor if irritation persists.

#### After eye contact:

Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Do not apply neutralizing agents. Take victim to an ophthalmologist if irritation persists.

#### After ingestion:

Rinse mouth with water. Immediately after ingestion: give lots of water to drink. Do not induce vomiting. Consult a doctor/medical service if you feel

#### 4.2. Most important symptoms and effects, both acute and delayed

#### 4.2.1 Acute symptoms

#### After inhalation:

Dry/sore throat. Coughing. Irritation of the respiratory tract. Irritation of the nasal mucous membranes. Runny nose. FOLLOWING SYMPTOMS MAY APPEAR LATER: Possible inflammation of the respiratory tract. Risk of lung oedema. Respiratory difficulties.

After skin contact: Tingling/irritation of the skin. After eye contact: Irritation of the eye tissue. Lacrimation. After ingestion:

#### Not applicable.

- 4.2.2 Delayed symptoms No effects known.
- **4.3. Indication of any immediate medical attention and special treatment needed** If applicable and available it will be listed below.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

5.1.1 Suitable extinguishing media:

Small fire: Quick-acting ABC powder extinguisher, Quick-acting BC powder extinguisher.

5.1.2 Unsuitable extinguishing media:

Small fire: Quick-acting CO2 extinguisher, Water (water can be used to control jet flame), Foam. Major fire: Water (water can be used to control jet flame), Foam.

#### 5.2. Special hazards arising from the substance or mixture

On burning: release of toxic and corrosive gases/vapours (nitrous vapours, hydrogen chloride, carbon monoxide - carbon dioxide). Pressurised container: May burst if heated. May polymerize on exposure to temperature rise. On heating: release of toxic/combustible gases/vapours (hydrogen cyanide).

#### 5.3. Advice for firefighters

#### 5.3.1 Instructions:

If exposed to fire cool the closed containers by spraying with water. Physical explosion risk: extinguish/cool from behind cover. Do not move the load if exposed to heat. After cooling: persistant risk of physical explosion. Dilute toxic gases with water spray. Take account of toxic/corrosive precipitation water.

#### 5.3.2 Special protective equipment for fire-fighters:

Gloves. Protective goggles. Head/neck protection. Protective clothing. Heat/fire exposure: compressed air/oxygen apparatus.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Stop engines and no smoking. No naked flames or sparks. Spark- and explosionproof appliances and lighting equipment.

- 6.1.1 Protective equipment for non-emergency personnel
  - See heading 8.2

#### 6.1.2 Protective equipment for emergency responders

Gloves. Protective goggles. Head/neck protection. Protective clothing.

#### Suitable protective clothing

See heading 8.2

#### 6.2. Environmental precautions

Dam up the solid spill. Use appropriate containment to avoid environmental contamination.

Reason for revision: 2.2

Publication date: 2017-06-02 Date of revision: 2017-12-17

#### 6.3. Methods and material for containment and cleaning up

Allow product to solidify and remove it by mechanical means. Carefully collect the spill/leftovers. Clean (treat) contaminated surfaces with acetone. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

#### 6.4. Reference to other sections

See heading 13.

### SECTION 7: Handling and storage

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

#### 7.1. Precautions for safe handling

Use spark-/explosionproof appliances and lighting system. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Observe very strict hygiene - avoid contact. Remove contaminated clothing immediately.

#### 7.2. Conditions for safe storage, including any incompatibilities

#### 7.2.1 Safe storage requirements:

Storage temperature: < 50 °C. Store in a cool area. Keep out of direct sunlight. Store in a dry area. Ventilation at floor level. Fireproof storeroom. Unauthorized persons are not admitted. Meet the legal requirements. Max. storage time: 1 year(s).

#### 7.2.2 Keep away from:

Heat sources, ignition sources, (strong) acids, (strong) bases.

- 7.2.3 Suitable packaging material:
  - Aerosol.

#### 7.2.4 Non suitable packaging material:

No data available

#### 7.3. Specific end use(s)

If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

#### 8.1.1 Occupational exposure

a) Occupational exposure limit values

If limit values are applicable and available these will be listed below.

EU

20		
Dimethylether	Time-weighted average exposure limit 8 h (Indicative occupational	1000 ppm
	exposure limit value)	
	Time-weighted average exposure limit 8 h (Indicative occupational	1920 mg/m³
	exposure limit value)	

bolgium		
4,4'-Diisocyanate de diphénylméthane (MDI)	Time-weighted average exposure limit 8 h	0.005 ppm
	Time-weighted average exposure limit 8 h	0.052 mg/m³
Hydrocarbures aliphatiques sous forme gazeuse : (Alcanes C1- C4)	Time-weighted average exposure limit 8 h	1000 ppm
Oxyde de diméthyle	Time-weighted average exposure limit 8 h	1000 ppm
	Time-weighted average exposure limit 8 h	1920 mg/m³

The Netherlands

Dimethylether	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	496 ppm
	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	950 mg/m³
	Short time value (Public occupational exposure limit value)	783 ppm
	Short time value (Public occupational exposure limit value)	1500 mg/m <sup>3</sup>

	Time-weighted average exposure limit 8 h (VL: Valeur non	0.1 mg/m³
	réglementaire indicative)	
	Short time value (VL: Valeur non réglementaire indicative)	0.02 ppm
	Short time value (VL: Valeur non réglementaire indicative)	0.2 mg/m³
Oxyde de diméthyle	Time-weighted average exposure limit 8 h (VRI: Valeur réglementaire indicative)	1000 ppm
	Time-weighted average exposure limit 8 h (VRI: Valeur réglementaire indicative)	1920 mg/m³

#### Germany

Reason for revision: 2.2

Publication date: 2017-06-02 Date of revision: 2017-12-17

Revision number: 0003

4,4'-Methylendiphenyldiisocyan Chloralkane, C14-17 (Chlorierte Dimethylether Isobutan				e exposure limit 8 h (TRO		0.05 mg/m
Dimethylether	,		Time-weighted average exposure limit 8 h (TRGS 900)		0.3 ppm	
				e exposure limit 8 h (TRG		6 mg/m <sup>3</sup>
			<u> </u>	e exposure limit 8 h (TRO		1000 ppm
Isobutan				e exposure limit 8 h (TRC		1900 mg/r
isobutan			0 0	e exposure limit 8 h (TRO	1	1000 ppm
				e exposure limit 8 h (TRO		2400 mg/r
MDI (als MDI berechnet)				e exposure limit 8 h (TRO		0.05 mg/m
Propan				e exposure limit 8 h (TRO		1000 ppm
•				e exposure limit 8 h (TRC		1800 mg/r
				· · · · ·	,	0,
UK						
Dimethyl ether				e exposure limit 8 h (Wo	rkplace exposure limit	400 ppm
		·	H40/2005))	e exposure limit 8 h (Wo	rkalaga aynagyra limit	766 mg/m
			H40/2005))	e exposure innit 8 n (wo	rikplace exposure inflic	700 mg/m
		·		kplace exposure limit (EF	140/2005))	500 ppm
				kplace exposure limit (EF		958 mg/m
socyanates, all (as -NCO) Excep	t methyl isocyanate			e exposure limit 8 h (Wo		0.02 mg/n
	e meen yn isoe yn indee		H40/2005))			0.02 116/11
				kplace exposure limit (EF	140/2005))	0.07 mg/n
		<b>–</b> – – – – – – – – – – – – – – – – – –		, p	, <i>1</i> 1	
JSA (TLV-ACGIH)		<u> </u>				
Butane, all isomers			ort time value (TLV -	1 1		1000 ppm
Methylene bisphenyl isocyanate	e (MDI)	Ti	me-weighted averag	e exposure limit 8 h (TLV	' - Adopted Value)	0.005 ppm
) National biological limit value	es					
f limit values are applicable and		be listed belo	w.			
2 Sampling methods						
Product name			Test	Number		
socianatos			NIOSH	5521		
Isocyanates			NIOSH	5522		
·	-					
socyanates	using the substance	or mixture a	s intended	•		
socyanates 3 Applicable limit values when f limit values are applicable and 4 DNEL/PNEC values DNEL/DMEL - Workers	using the substance available these will	e or mixture a be listed belo	s intended w.			
socyanates Applicable limit values when the f limit values are applicable and I DNEL/PNEC values <u>DNEL/DMEL - Workers</u> <u>Ikanes, C14-17, chloro</u> Effect level (DNEL/DMEL)	available these will	be listed belo	w.	Value	Remark	
socyanates Applicable limit values when limit values are applicable and DNEL/PNEC values NEL/DMEL - Workers Ikanes, C14-17, chloro	available these will Type Long-term syst	be listed belo	w. inhalation	6.7 mg/m <sup>3</sup>		
socyanates <b>3 Applicable limit values when</b> i f limit values are applicable and <b>4 DNEL/PNEC values</b> <b>5 DNEL/DMEL - Workers</b> <b>1 Ikanes, C14-17, chloro</b> <b>5 Effect level (DNEL/DMEL)</b> DNEL	Type Long-term syst	be listed belo	w. inhalation			
socyanates 3 Applicable limit values when i f limit values are applicable and 4 DNEL/PNEC values DNEL/DMEL - Workers Ilkanes, C14-17, chloro Effect level (DNEL/DMEL) DNEL DNEL	Type Long-term syst	be listed belo	w. inhalation	6.7 mg/m <sup>3</sup>		
socyanates <b>Applicable limit values when</b> i f limit values are applicable and <b>I DNEL/PNEC values</b> <b>DNEL/DMEL - Workers</b> Ilkanes, C14-17, chloro <b>Effect level (DNEL/DMEL)</b> DNEL DNEL DNEL-DMEL - General population Ilkanes, C14-17, chloro	Type Long-term syst Long-term syst	be listed belo	w. inhalation	6.7 mg/m³ 47.9 mg/kg bw/r	day	
socyanates <b>Applicable limit values when</b> i f limit values are applicable and <b>I DNEL/PNEC values</b> <b>DNEL/DMEL - Workers</b> Ilkanes, C14-17, chloro Effect level (DNEL/DMEL) DNEL DNEL/DMEL - General population Ilkanes, C14-17, chloro Effect level (DNEL/DMEL)	Type Long-term syst Long-term syst Dn Type	be listed belo temic effects temic effects	inhalation dermal	6.7 mg/m <sup>3</sup> 47.9 mg/kg bw/r Value		
socyanates 3 Applicable limit values when i f limit values are applicable and 4 DNEL/PNEC values DNEL/DMEL - Workers Ilkanes, C14-17, chloro Effect level (DNEL/DMEL) DNEL DNEL DNEL-DMEL - General population Ilkanes, C14-17, chloro	Type Long-term syst Long-term syst Don Type Long-term syst	be listed belo temic effects temic effects temic effects	inhalation dermal inhalation	6.7 mg/m <sup>3</sup> 47.9 mg/kg bw/n Value 2 mg/m <sup>3</sup>	day Remark	
socyanates Applicable limit values when i f limit values are applicable and DNEL/PNEC values DNEL/DMEL - Workers Ilkanes, C14-17, chloro Effect level (DNEL/DMEL) DNEL DNEL/DMEL - General population Ilkanes, C14-17, chloro Effect level (DNEL/DMEL)	Type Long-term syst Long-term syst Don Type Long-term syst Long-term syst	be listed belo temic effects temic effects temic effects temic effects	inhalation dermal inhalation dermal	6.7 mg/m <sup>3</sup> 47.9 mg/kg bw/v Value 2 mg/m <sup>3</sup> 28.75 mg/kg bw	day Remark	
socyanates Applicable limit values when i f limit values are applicable and DNEL/PNEC values DNEL/DMEL - Workers Ilkanes, C14-17, chloro Effect level (DNEL/DMEL) DNEL DNEL/DMEL - General population Ilkanes, C14-17, chloro Effect level (DNEL/DMEL) DNEL	Type Long-term syst Long-term syst Don Type Long-term syst	be listed belo temic effects temic effects temic effects temic effects	inhalation dermal inhalation dermal	6.7 mg/m <sup>3</sup> 47.9 mg/kg bw/n Value 2 mg/m <sup>3</sup>	day Remark	
Socyanates Applicable limit values when i f limit values are applicable and DNEL/PNEC values DNEL/DMEL - Workers Ikanes, C14-17, chloro Effect level (DNEL/DMEL) DNEL DNEL DNEL/DMEL - General populatio Ikanes, C14-17, chloro Effect level (DNEL/DMEL) DNEL DNEL DNEL	Type Long-term syst Long-term syst Don Type Long-term syst Long-term syst	be listed belo temic effects temic effects temic effects temic effects	inhalation dermal inhalation dermal	6.7 mg/m <sup>3</sup> 47.9 mg/kg bw/v Value 2 mg/m <sup>3</sup> 28.75 mg/kg bw	day Remark	
socyanates Applicable limit values when it limit values are applicable and DNEL/PNEC values DNEL/DMEL - Workers Ikanes, C14-17, chloro Effect level (DNEL/DMEL) DNEL DNEL DNEL/DMEL - General population Ikanes, C14-17, chloro Effect level (DNEL/DMEL) DNEL DNEL Ikanes, C14-17, chloro	Type Long-term syst Long-term syst Don Type Long-term syst Long-term syst	temic effects temic effects temic effects temic effects temic effects	inhalation dermal inhalation dermal	6.7 mg/m <sup>3</sup> 47.9 mg/kg bw/r 2 mg/m <sup>3</sup> 28.75 mg/kg bw/r 0.58 mg/kg bw/r	day Remark /day day day	
Isocyanates 3 Applicable limit values when i f limit values are applicable and 4 DNEL/PNEC values DNEL/DMEL - Workers alkanes, C14-17, chloro Effect level (DNEL/DMEL) DNEL DNEL DNEL/DMEL - General population alkanes, C14-17, chloro Effect level (DNEL/DMEL) DNEL PNEC alkanes, C14-17, chloro Compartments	Type Long-term syst Long-term syst Don Type Long-term syst Long-term syst	temic effects temic effects temic effects temic effects temic effects temic effects	inhalation dermal inhalation dermal	6.7 mg/m <sup>3</sup> 47.9 mg/kg bw/r 2 mg/m <sup>3</sup> 28.75 mg/kg bw/r 0.58 mg/kg bw/r	day Remark	
socyanates 3 Applicable limit values when i f limit values are applicable and 4 DNEL/PNEC values DNEL/DMEL - Workers alkanes, C14-17, chloro Effect level (DNEL/DMEL) DNEL DNEL/DMEL - General population alkanes, C14-17, chloro Effect level (DNEL/DMEL) DNEL DNEL DNEL DNEL DNEL Effect level (DNEL/DMEL) DNEL DNEL Effect level (DNEL/DMEL) DNEL Effect level (DNEL/DMEL) DNEL Effect level (DNEL/DMEL) DNEL PNEC Alkanes, C14-17, chloro Compartments Fresh water	Type Long-term syst Long-term syst Don Type Long-term syst Long-term syst	temic effects temic effects temic effects temic effects temic effects temic effects temic effects	inhalation dermal inhalation dermal	6.7 mg/m <sup>3</sup> 47.9 mg/kg bw/r 2 mg/m <sup>3</sup> 28.75 mg/kg bw/r 0.58 mg/kg bw/r	day Remark /day day day	
Socyanates Applicable limit values when i f limit values are applicable and DNEL/PNEC values DNEL/DMEL - Workers Ilkanes, C14-17, chloro Effect level (DNEL/DMEL) DNEL DNEL DNEL/DMEL - General population Ilkanes, C14-17, chloro Effect level (DNEL/DMEL) DNEL DNEL DNEL DNEL Compartments Fresh water Marine water	Type Long-term syst Long-term syst Don Type Long-term syst Long-term syst	temic effects temic effects temic effects temic effects temic effects temic effects temic effects temic effects temic effects	inhalation dermal inhalation dermal	6.7 mg/m <sup>3</sup> 47.9 mg/kg bw/r 2 mg/m <sup>3</sup> 28.75 mg/kg bw/r 0.58 mg/kg bw/r	day Remark /day day day	
Socyanates Applicable limit values when it limit values are applicable and DNEL/PNEC values DNEL/DMEL - Workers Ikanes, C14-17, chloro Effect level (DNEL/DMEL) DNEL DNEL DNEL - General population Ikanes, C14-17, chloro Effect level (DNEL/DMEL) DNEL DNEL DNEL Effect sevel (DNEL/DMEL) DNEL DNEL Compartments Fresh water Marine water STP	Type Long-term syst Long-term syst Don Type Long-term syst Long-term syst	temic effects temic effects temic effects temic effects temic effects temic effects temic effects temic effects temic effects temic effects	w. inhalation dermal inhalation dermal oral	6.7 mg/m <sup>3</sup> 47.9 mg/kg bw/r 2 mg/m <sup>3</sup> 28.75 mg/kg bw/r 0.58 mg/kg bw/r	day Remark /day day day	
socyanates Applicable limit values when i f limit values are applicable and DNEL/PNEC values DNEL/DMEL - Workers Ilkanes, C14-17, chloro Effect level (DNEL/DMEL) DNEL DNEL DNEL DNEL DNEL Compartments Fresh water Marine water STP Fresh water sediment	Type Long-term syst Long-term syst Don Type Long-term syst Long-term syst	temic effects temic effects	w. inhalation dermal inhalation dermal oral ediment dw	6.7 mg/m <sup>3</sup> 47.9 mg/kg bw/r 2 mg/m <sup>3</sup> 28.75 mg/kg bw/r 0.58 mg/kg bw/r	day Remark /day day day	
socyanates 3 Applicable limit values when i f limit values are applicable and 4 DNEL/PNEC values DNEL/DMEL - Workers alkanes, C14-17, chloro Effect level (DNEL/DMEL) DNEL DNEL DNEL DNEL DNEL Effect level (DNEL/DMEL) DNEL DNEL PNEC alkanes, C14-17, chloro Compartments Fresh water Marine water STP Fresh water sediment Marine water sediment	Type Long-term syst Long-term syst Don Type Long-term syst Long-term syst	temic effects temic effects	w. inhalation dermal inhalation dermal oral ediment dw sediment dw	6.7 mg/m <sup>3</sup> 47.9 mg/kg bw/r 2 mg/m <sup>3</sup> 28.75 mg/kg bw/r 0.58 mg/kg bw/r	day Remark /day day day	
socyanates 3 Applicable limit values when i f limit values are applicable and 4 DNEL/PNEC values DNEL/DMEL - Workers alkanes, C14-17, chloro Effect level (DNEL/DMEL) DNEL DNEL DNEL DNEL DNEL Effect level (DNEL/DMEL) DNEL DNEL DNEL DNEL PNEC alkanes, C14-17, chloro Compartments Fresh water Marine water STP Fresh water sediment Marine water sediment Soil	Type Long-term syst Long-term syst Don Type Long-term syst Long-term syst	be listed belo temic effects temic effects temi	w. inhalation dermal inhalation dermal oral oral ediment dw sediment dw soil dw	6.7 mg/m <sup>3</sup> 47.9 mg/kg bw/r 2 mg/m <sup>3</sup> 28.75 mg/kg bw/r 0.58 mg/kg bw/r	day Remark /day day day	
Isocyanates 3 Applicable limit values when i f limit values are applicable and 4 DNEL/PNEC values DNEL/DMEL - Workers alkanes, C14-17, chloro Effect level (DNEL/DMEL) DNEL DNEL DNEL DNEL DNEL COMPACTION Effect level (DNEL/DMEL) DNEL DNEL PNEC alkanes, C14-17, chloro Compartments Fresh water Marine water STP Fresh water sediment Marine water sediment	Type Long-term syst Long-term syst Don Type Long-term syst Long-term syst	temic effects temic effects	w. inhalation dermal inhalation dermal oral oral ediment dw sediment dw soil dw	6.7 mg/m <sup>3</sup> 47.9 mg/kg bw/r 2 mg/m <sup>3</sup> 28.75 mg/kg bw/r 0.58 mg/kg bw/r	day Remark /day day day	
Isocyanates 3 Applicable limit values when i if limit values are applicable and 4 DNEL/PNEC values DNEL/DMEL - Workers alkanes, C14-17, chloro Effect level (DNEL/DMEL) DNEL DNEL DNEL DNEL DNEL COMPARTMENTS Fresh water Marine water STP Fresh water sediment Marine water sediment Soil	Type Long-term syst Long-term syst Don Type Long-term syst Long-term syst	be listed belo temic effects temic effects temi	w. inhalation dermal inhalation dermal oral oral ediment dw sediment dw soil dw	6.7 mg/m <sup>3</sup> 47.9 mg/kg bw/r 2 mg/m <sup>3</sup> 28.75 mg/kg bw/r 0.58 mg/kg bw/r	day Remark /day day day	

Date of revision: 2017-12-17

Protective goggles.

d) Skin protection:

Head/neck protection. Protective clothing.

8.2.3 Environmental exposure controls:

See headings 6.2, 6.3 and 13

### SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical form	Aerosol
Odour	Characteristic odour
Odour threshold	No data available
Colour	Variable in colour, depending on the composition
Particle size	Not applicable
Explosion limits	No data available
Flammability	Extremely flammable aerosol.
Log Kow	Not applicable (mixture)
Dynamic viscosity	No data available
Kinematic viscosity	No data available
Melting point	No data available
Boiling point	No data available
Flash point	Not applicable
Evaporation rate	No data available
Relative vapour density	>1
Vapour pressure	No data available
Solubility	Organic solvents ; soluble
	Water ; insoluble
Relative density	0.95 ; 20 °C
Decomposition temperature	No data available
Auto-ignition temperature	No data available
Explosive properties	No chemical group associated with explosive properties
Oxidising properties	No chemical group associated with oxidising properties
рН	No data available

#### 9.2. Other information Absolute density

946.8 kg/m<sup>3</sup> ; 20 °C

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

May be ignited by sparks. Gas/vapour spreads at floor level: ignition hazard.

#### 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

May polymerize with many compounds e.g.: (strong) bases and amines. Reacts violently with (some) acids/bases.

#### 10.4. Conditions to avoid

Precautionary measures

Use spark-/explosionproof appliances and lighting system. Keep away from naked flames/heat. Keep away from ignition sources/sparks.

#### 10.5. Incompatible materials

(strong) acids, (strong) bases.

#### 10.6. Hazardous decomposition products

On heating: release of toxic/combustible gases/vapours (hydrogen cyanide). On burning: release of toxic and corrosive gases/vapours (nitrous vapours, hydrogen chloride, carbon monoxide - carbon dioxide).

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

11.1.1 Test results

#### Acute toxicity

GISS MOUSSE PU [610342]

Reason for revision: 2.2

Publication date: 2017-06-02 Date of revision: 2017-12-17

No (test)data on the mixture available

Classification of the mixture is based on the bridging principle

#### alkanes, C14-17, chloro

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value	Remark
						determination	
Oral	LD50		> 4000 mg/kg bw		Rat (male/female)	Experimental value	
Dermal	LD50		> 13500 mg/kg bw	24 h	Rabbit	Read-across	
Inhalation (vapours)	LC50		> 48.170 mg/l air	1 h	Rat	Read-across	

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value	Remark
						determination	
Oral	LD50		> 10000 mg/kg		Rat	Literature study	
Dermal	LD50		> 5000 mg/kg		Rabbit	Literature study	
Inhalation (vapours)	LD50		10 mg/l - 20 mg/l	4 h	Rat	Literature study	
Inhalation			category 4			Literature study	

Conclusion

Harmful if inhaled.

Not classified as acute toxic if swallowed

Not classified as acute toxic in contact with skin

#### Corrosion/irritation

#### GISS MOUSSE PU [610342]

No (test)data on the mixture available

Classification is based on the relevant ingredients

#### alkanes, C14-17, chloro

Route of exposure	Result	Method	Exposure time	Time point		Value determination	Remark
Eye	Slightly irritating				Rabbit	Expert judgement	
Skin	Slightly irritating	OECD 404	4 h	24; 72 hours	Rabbit	Expert judgement	

#### polymethylene polyphenyl isocyanate

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Irritating; category 2					Literature study	
Skin	Irritating; category 2					Literature study	
Inhalation	Irritating; STOT SE cat.3					Literature study	

#### Conclusion

Causes skin irritation.

Causes serious eye irritation.

May cause respiratory irritation.

#### Respiratory or skin sensitisation

#### GISS MOUSSE PU [610342]

#### No (test)data on the mixture available

Classification is based on the relevant ingredients

category 1

#### alkanes, C14-17, chloro

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	Guinea pig maximisation test		48 hours	Guinea pig	Experimental value	
olymethylene polyp	phenyl isocyanate		•				
Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Sensitizing; category 1					Literature study	
Inhalation	Sensitizing;					Literature study	

#### Conclusion

#### May cause an allergic skin reaction.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

#### Specific target organ toxicity

#### GISS MOUSSE PU [610342]

Reason for revision: 2.2

Publication date: 2017-06-02 Date of revision: 2017-12-17

Revision number: 0003

No (test)data on the mixture available

Classification is based on the relevant ingredients

#### alkanes, C14-17, chloro

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral (diet)	NOAEL	Equivalent to OECD 408	300 ppm		No effect	13 weeks (daily)	Rat (male/female)	Experimental value
Oral (diet)	NOAEL		23 mg/kg bw/day - 24.6 mg/kg bw/day		No effect	13 weeks (daily)	Rat (male/female)	Experimental value
Dermal								Data waiving
Inhalation								Data waiving

#### polymethylene polyphenyl isocyanate

Route of exposi	re Parameter	Method	Value	Organ	Effect	Exposure time	 Value determination
Inhalation			STOT RE cat.2				Literature study

#### Conclusion

May cause damage to organs through prolonged or repeated exposure if inhaled.

Not classified as sub-chronically toxic in contact with skin

Not classified as sub-chronically toxic if swallowed

#### Mutagenicity (in vitro)

GISS MOUSSE PU [610342]

No (test)data on the mixture available

#### alkanes, C14-17, chloro

Result	Method	Test substrate	Effect	Value determination
Negative with metabolic activation, negative without	OECD 471	Bacteria (S.typhimurium)	No effect	Experimental value
metabolic activation				

#### Mutagenicity (in vivo)

#### GISS MOUSSE PU [610342]

No (test)data on the mixture available

Classification is based on the relevant ingredients

#### alkanes, C14-17, chloro

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative	Equivalent to OECD 475	5 day(s)	Rat (male)	Bone marrow	Experimental value
Negative	Equivalent to OECD 474		Mouse (male/female)	Bone marrow	Experimental value

#### Conclusion

Not classified for mutagenic or genotoxic toxicity

#### Carcinogenicity

#### GISS MOUSSE PU [610342]

No (test)data on the mixture available

Classification is based on the relevant ingredients

#### alkanes, C14-17, chloro

Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Oral	LOAEL	Equivalent to OECD 451	312 mg/kg bw/day	104 weeks (5 days/week)	Rat (male/female)	Carcinogenicity	Liver; kidney	Read-across
Oral	LOAEL	Equivalent to OECD 451	312 mg/kg bw/day	103 weeks (5 days/week)	Rat (male/female)	Carcinogenicity	Thyroid	Read-across
methylene p	olyphenyl isoc	<u>yanate</u>						

Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	 Value determination
Unknown			category 2				Literature study

Conclusion

Suspected of causing cancer.

#### Reproductive toxicity

#### GISS MOUSSE PU [610342]

No (test)data on the mixture available

Classification is based on the relevant ingredients

Reason for revision: 2.2

	Parameter	Method	Value	Exposure time	Species	Effect	5	Value determination
Developmental toxicity	NOAEL	Equivalent to OECD 414	5000 mg/kg bw/day	14 days (gestation, daily)	Rat	No effect		Experimental value
Maternal toxicity	NOAEL	Equivalent to OECD 414	500 mg/kg bw/day	13 days (gestation, daily)	Rat	No effect		Experimental value
Effects on fertility	NOAEL (P)	OECD 421	100 mg/kg bw/day	9 week(s)	Rat (male)	No effect		Experimental value
	NOAEL (P)	OECD 421	100 mg/kg bw/day	11 week(s) - 12 week(s)	Rat (female)	No effect		Experimental value
Effects on lactation	LOAEL		3125 mg/kg bw		Rat (male/female)	Increased mortality in the pups		Experimental value

#### Conclusion

May cause harm to breast-fed children.

Not classified for reprotoxic or developmental toxicity

#### Toxicity other effects

#### GISS MOUSSE PU [610342]

No (test)data on the mixture available

alkanes, C14-17, chloro

Parameter	Method	Value	Organ	Effect	Exposure time		Value determination
	Other		Skin	Skin dryness or cracking		Rat	Experimental value

#### Chronic effects from short and long-term exposure

#### GISS MOUSSE PU [610342]

ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: Feeling of weakness. Itching. Skin rash/inflammation. May stain the skin. Dry skin. Coughing. Possible inflammation of the respiratory tract. Respiratory difficulties.

### SECTION 12: Ecological information

#### 12.1. Toxicity

GISS MOUSSE PU [610342]

No (test)data on the mixture available

Classification is based on the relevant ingredients

Reason for revision: 2.2

Publication date: 2017-06-02 Date of revision: 2017-12-17

Revision number: 0003

	Parameter	Method	Value	Duration	Sp	ecies	Test design	Fresh/salt water	Value determinatio
Acute toxicity fishes	LC50	Equivalent to OECD 203	> 5000 mg/	/l 96 h		ournus ournus	Static syster	n Brackish water	Experimental value; Nominal concentration
Acute toxicity crustacea	EC50	OECD 202	0.006 mg/l	48 h	Da	phnia magna	Static syster	n Fresh water	Experimental value; GLP
Foxicity algae and other aquatic plants	NOEC	OECD 201	0.1 mg/l	96 h		eudokirchnerie subcapitata	Static syster	n Fresh water	Experimental value; GLP
	ErC50	OECD 201	> 3.2 mg/l	72 h		eudokirchnerie subcapitata	Static syster	n Fresh water	Experimental value; GLP
ong-term toxicity fish	NOEC	Equivalent to OECD 204	> 125 µg/l	14 day(s)			Semi-static system	Brackish water	Experimental value
Long-term toxicity aquatic crustacea	NOEC	OECD 202	0.01 mg/l	21 day(s)	Da	phnia magna	Static syster	n Fresh water	Experimental value
	Parameter	Method		Value		Duration	Spec	ies	Value determination
Foxicity soil macro-organisms	NOEC	OECD 222		900 mg/kg soil	dw	56 day(s)	Eiser	iia fetida	Experimental value
Toxicity soil micro-organisms	NOEC	OECD 216		≥ 400 mg/kg so	il dw	28 day(s)	Soil ı	nicro-organisms	Experimental value
	EC50	OECD 216		> 400 mg/kg so	il dw	28 day(s)	Soil ı	nicro-organisms	Experimental value
Toxicity terrestrial plants	NOEC	OECD 208		≥ 5000 mg/l		28 day(s)	Bras	sica napus	Experimental value
Toxicity birds	LC50	Equivalent 205	to OECD	> 24603 mg/kg	food	5 day(s)	Phas	ianus colchicus	Experimental value
	NOEC	Equivalent 205	to OECD	24603 mg/kg fo	od	5 day(s)	Phas	ianus colchicus	Experimental value
lymethylene polyphenyl isocyar	nate	· · ·							
	Parameter	Method	Value	Duration	Sn	ecies	Test design	Fresh/salt	Value determinati

	Parameter	Method	Value	Duration	Species	 Fresh/salt water	Value determination
Acute toxicity other aquatic organisms	LC50		> 1000 mg/l	96 h			Literature study
Toxicity aquatic micro- organisms	EC50	OECD 209	> 100 mg/l		Activated sludge		Literature study

#### **Conclusion**

May cause long lasting harmful effects to aquatic life.

#### 12.2. Persistence and degradability

#### alkanes, C14-17, chloro

Biodegradation wa	ter
-------------------	-----

Method	Value	Duration	Value determination
OECD 301D: Closed Bottle Test	37 %; GLP	28 day(s)	Experimental value
Biodegradation soil			· · · · · · · · · · · · · · · · · · ·
Method	Value	Duration	Value determination
	51 % - 57 %	36 h	Experimental value

#### polymethylene polyphenyl isocyanate

ы	odegradation water			
	Method	Value	Duration	Value determination
	OECD 302C: Inherent Biodegradability: Modified MITI Test (II)	< 60 %		Experimental value

#### **Conclusion**

Contains non readily biodegradable component(s)

#### 12.3. Bioaccumulative potential

#### GISS MOUSSE PU [610342]

Log Kow

Method	Remark	Value	Temperature	Value determination
	Not applicable (mixture)			

Reason for revision: 2.2

Parameter	Method	Value	Duration	Species		Value determination
BCF	OECD 305	6660	35 day(s)	Oncorhy	nchus mykiss	Experimental value
og Kow						
Method	Rem	ark	Value		Temperature	Value determination
			5.47 - 8.01			Experimental value
			> 5			
methylene pol	<u>yphenyl isocyanate</u>					
CF fishes						
Parameter	Method	Value	Duration	Species		Value determination
BCF		1		Pisces		Literature study
g Kow						
g Kow Method	Rem	ark	Value		Temperature	Value determination
		ark lata available	Value		Temperature	Value determination
			Value		Temperature	Value determination
Method usion		lata available	Value		Temperature	Value determination
Method usion tains bioaccum	No d	lata available	Value		Temperature	Value determination
Method usion tains bioaccum . Mobility ir	No d Iulative component(: N SOII	lata available	Value		Temperature	Value determination
Method usion tains bioaccum . Mobility ir nes, C14-17, ch	No d Iulative component(: N SOII	lata available	Value		Temperature	Value determination
Method usion tains bioaccum . Mobility ir nes, C14-17, ch og) Koc	No d Iulative component(: N SOII	lata available				
Method usion tains bioaccum . Mobility ir nes, C14-17, ch	No d Iulative component(: N SOII	lata available	Value Method		Temperature Value 5	Value determination Value determination Value determination Experimental value

#### 12.5. Results of PBT and vPvB assessment

Due to insufficient data no statement can be made whether the component(s) fulfil(s) the criteria of PBT and vPvB according to Annex XIII of Regulation (EC) No 1907/2006.

#### 12.6. Other adverse effects

#### GISS MOUSSE PU [610342]

#### Fluorinated greenhouse gases (Regulation (EU) No 517/2014)

None of the known components is included in the list of fluorinated greenhouse gases (Regulation (EU) No 517/2014)

Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009)

### SECTION 13: Disposal considerations

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

#### 13.1. Waste treatment methods

#### 13.1.1 Provisions relating to waste

#### **European Union**

Hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014 and Regulation (EU) No 2017/997.

Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC).

08 05 01\* (wastes not otherwise specified in 08: waste isocyanates).

16 05 04\* (gases in pressure containers and discarded chemicals: gases in pressure containers (including halons) containing hazardous substances). Depending on branch of industry and production process, also other waste codes may be applicable.

#### 13.1.2 Disposal methods

Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Specific treatment. Do not discharge into drains or the environment.

#### 13.1.3 Packaging/Container

#### **European Union**

Waste material code packaging (Directive 2008/98/EC).

15 01 10\* (packaging containing residues of or contaminated by dangerous substances).

### SECTION 14: Transport information

#### Road (ADR) 14.1. UN number

14.1. 011 11011001	
UN number	1950
14.2. UN proper shipping name	
Proper shipping name	Aerosols
14.3. Transport hazard class(es)	

Reason for revision: 2.2

Publication date: 2017-06-02 Date of revision: 2017-12-17

Hazard identification number	
Class	2
Classification code	5F
.4.4. Packing group	
Packing group	
Labels	2.1
4.5. Environmental hazards	
Environmentally hazardous substance mark	no
4.6. Special precautions for user	
Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for
	liquids. A package shall not weigh more than 30 kg. (gross mass)

#### Rail (RID)

14.1. UN number	
UN number	1950
14.2. UN proper shipping name	
Proper shipping name	Aerosols
14.3. Transport hazard class(es)	
Hazard identification number	23
Class	2
Classification code	5F
14.4. Packing group	
Packing group	
Labels	2.1
14.5. Environmental hazards	
Environmentally hazardous substance mark	no
14.6. Special precautions for user	
Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for
	liquids. A package shall not weigh more than 30 kg. (gross mass)

#### Inland waterways (ADN)

14.1. UN number	
UN number	1950
14.2. UN proper shipping name	
Proper shipping name	Aerosols
14.3. Transport hazard class(es)	
Class	2
Classification code	5F
14.4. Packing group	
Packing group	
Labels	2.1
14.5. Environmental hazards	
Environmentally hazardous substance mark	no
14.6. Special precautions for user	
Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging fo liquids. A package shall not weigh more than 30 kg. (gross mass)

### Sea (IMDG/IMSBC)

14.1. UN number	
UN number	1950
14.2. UN proper shipping name	
Proper shipping name	Aerosols
14.3. Transport hazard class(es)	
Class	2.1
14.4. Packing group	
Packing group	
Labels	2.1

Reason for revision: 2.2

Publication date: 2017-06-02 Date of revision: 2017-12-17

Marine pollutant	-
Environmentally hazardous substance mark	no
6. Special precautions for user	
Special provisions	63
Special provisions	190
Special provisions	277
Special provisions	327
Special provisions	344
Special provisions	381
Special provisions	959
Limited quantities	Combination packagings: not more than 1 liter per inner packaging fo
	liquids. A package shall not weigh more than 30 kg. (gross mass)
7. Transport in bulk according to Annex II of Marpol and the	IBC Code
Annex II of MARPOL 73/78	Not applicable

#### Air (ICAO-TI/IATA-DGR)

14.1. UN number	
UN number	1950
14.2. UN proper shipping name	
Proper shipping name	Aerosols, flammable
14.3. Transport hazard class(es)	
Class	2.1
14.4. Packing group	
Packing group	
Labels	2.1
14.5. Environmental hazards	
Environmentally hazardous substance mark	no
14.6. Special precautions for user	
Special provisions	A145
Special provisions	A167
Special provisions	A802
Limited quantities: maximum net quantity per packaging	30 kg G

### SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### European legislation:

VOC content Directive 2010/75/EU

VOC content	Remark
18.894 % - 26.517 %	
178.888 g/l - 251.063 g/l	

**REACH Annex XVII - Restriction** 

Contains component(s) subject to restrictions of Annex XVII of Regulation (EC) No 1907/2006: restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.

polymethylene polyphenyl isocyanate regarded as dangerous in accordance with Directive 1999/45/EC or are fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: (a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F; (b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on	1. Shall not be used in:
effects, 3.9 and 3.10; (c) hazard class 4.1; (d) hazard class 5.1.	<ul> <li>ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,</li> <li>tricks and jokes,</li> <li>games for one or more participants, or any article intended to be used as such, even with ornamental aspects,</li> <li>Articles not complying with paragraph 1 shall not be placed on the market.</li> <li>Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they:</li> <li>can be used as fuel in decorative oil lamps for supply to the general public, and,</li> <li>present an aspiration hazard and are labelled with R65 or H304,</li> <li>Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopte by the European Committee for Standardisation (CEN).</li> <li>S. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of dangerous substances and mixtures, suppliers shat ensure, before the placing on the market, that the following requirements are met:</li> <li>a) lamp oils, labelled with R65 or H304, intended for supply to the general public are visibly legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach children"; and, by 1 December 2010, "Just a sip of lamp oil — or even sucking the wick of lamps — may lead to life- threatening lung damage";</li> <li>b) grill lighter fluids, labelled with R65 or H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: "Just a sip of grill lighter may lead to life threatening lung damage";</li> <li>c) lamp oils and grill lighters, labelled with R65 or H304, intended for supply to the</li> </ul>
on for revision: 2.2	Publication date: 2017-06-02

Date of revision: 2017-12-17

	0133 10100331			
· polymethylene polyphenyl isocyanate	Methylenediphenyl diisocyanate (MDI) including the following specific isomers: 4,4'- Methylenediphenyl diisocyanate; 2,4'- Methylenediphenyl diisocyanate; 2,2'- Methylenediphenyl diisocyanate	general public are packaged in black opaque containers not exceeding 1 litre by 1 Decem 2010. 6. No later than 1 June 2014, the Commission shall request the European Chemicals Age to prepare a dossier, in accordance with Article 69 of the present Regulation with a view ban, if appropriate, grill lighter fluids and fuel for decorative lamps, labelled R65 or H304 intended for supply to the general public. 7. Natural or legal persons placing on the market for the first time lamp oils and grill light fluids, labelled with R65 or H304, shall by 1 December 2011, and annually thereafter, provide data on alternatives to lamp oils and grill lighter fluids labelled R65 or H304 to th competent authority in the Member State concerned. Member States shall make those or available to the Commission.' 1. Shall not be placed on the market after 27 December 2010, as a constituent of mixture concentrations equal to or greater than 0,1 % by weight of MDI for supply to the general public, unless suppliers shall ensure before the placing on the market that the packaging (a) contains protective gloves which comply with the requirements of Council Directive 89/686/EEC; (b) is marked visibly, legibly and indelibly as follows, and without prejudice to other Community legislation concerning the classification, packaging and labelling of substance and mixtures: <i>"</i> — Persons already sensitised to diisocyanates may develop allergic reactions when usir this product. — Persons suffering from asthma, eczema or skin problems should avoid contact, includ dermal contact, with this product. — This product should not be used under conditions of poor ventilation unless a protect mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used 2. By way of derogation, paragraph 1(a) shall not apply to hot melt adhesives.		
<u>National legislation Belgium</u> <u>GISS MOUSSE PU [610342]</u> No data available				
National legislation The Netherlan	<u>ds</u>			
GISS MOUSSE PU [610342]	Z (2)			
Waterbezwaarlijkheid	2 (2)			
<u>National legislation France</u> <u>GISS MOUSSE PU [610342]</u> No data available <u>polymethylene polyphenyl isoc</u>	<u>yanate</u>			
Catégorie cancérogène	4,4'-Diisocyanate de diphénylméthane;	C2		
National legislation Germany				
<u>GISS MOUSSE PU [610342]</u> WGK	2; Classification water polluting based o Stoffe (VwVwS) of 27 July 2005 (Anhang	n the components in compliance with Verwaltungsvorschrift wassergefährden		
alkanes, C14-17, chloro	Stone (vwvw3) of 27 July 2003 (Annang	<u>, 4)</u>		
TA-Luft	5.2.5; I			
TRGS900 - Risiko der		ne C14-17 ); Y; Risiko der Fruchtschädigung braucht bei Einhaltung des		
Fruchtschädigung Hautresorptive Stoffe	Chloralkane, C14-17 (Chlorierte Paraffir	ischen Grenzwertes nicht befürchtet zu werden		
polymethylene polyphenyl isoc				
TA-Luft	5.2.5; I			
TRGS900 - Risiko der Fruchtschädigung	4,4'-Methylendiphenyldiisocyanat; Y; Ris und des biologischen Grenzwertes nicht	siko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes thefürchtet zu werden		
	5	Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des		
Constitution of the	biologischen Grenzwertes nicht befürch			
Sensibilisierende Stoffe	4,4'-Methylendiphenyldiisocyanat; Sah; Zielorganen Allergien auslösende	Atemwegssensibilisierende Stoffe Und Hautsensibilisierende Stoffe, an beiden		
	pMDI (als MDI berechnet); Sa; Atemweg	zssensibilisierende Stoffe		
TRGS905 - Krebserzeugend	Techn. ("Polymeres") MDI (pMDI) (in Fo	Techn. ("Polymeres") MDI (pMDI) (in Form atembarer Aerosole, A-Fraktion); 2		
TRGS905 - Erbgutverändernd	Techn. ("Polymeres") MDI (pMDI) (in Fo			
TRGS905 - Fruchtbarkeitsgefährdend	Techn. ("Polymeres") MDI (pMDI) (in Fo	rm atemparer Aerosole, A-Fraktion); -		
TRGS905 - Fruchtschädigend	Techn. ("Polymeres") MDI (pMDI) (in Fo	rm atembarer Aerosole, A-Fraktion); -		
Hautresorptive Stoffe	4,4'-Methylendiphenyldiisocyanat; H; Hautresorptiv			
	pMDI (als MDI berechnet); H; Hautresor	puv		
<u>National legislation United Kingdo</u> <u>GISS MOUSSE PU [610342]</u> No data available	<u>m</u>			
polymethylene polyphenyl isoc	yanate			
Skin Sensitisation	Isocyanates, all (as -NCO) Except methy			
Respiratory sensitisation	Isocyanates, all (as -NCO) Except methy	l isocyanate; Sen		
son for revision: 2.2		Publication date: 2017-06-02		
		Date of revision: 2017-06-02		
		Desiduation (CA20 44/		

GISS MOUSSE PU [610342]				
Other relevant data				
GISS MOUSSE PU [	610342]			
No data available				
alkanes, C14-17, cl	nloro			
IARC - classificati				
polymethylene po	yphenyl isocyanate			
IARC - classificati	on 3; Polymethylene polyphe	nyl isocyanate		
5.2. Chemical safet	v assessment			
	assessment has been conducted for the	mixture.		
alkanes, C14-17, cl				
	assessment has been performed.			
TION 16: Othe	er information			
Full text of any H-stat	ements referred to under heading 3:			
H220 Extremely f				
H222 Extremely f				
	container: May burst if heated. s under pressure; may explode if heated			
H315 Causes skin		•		
H317 May cause	an allergic skin reaction.			
H319 Causes serie	ous eye irritation.			
H332 Harmful if in			ll	
	allergy or asthma symptoms or breathing respiratory irritation.	g difficulties if inha	iea.	
H335 May cause H351 Suspected of				
	harm to breast-fed children.			
	damage to organs through prolonged or	repeated exposure	e if inhaled.	
H400 Very toxic t				
	o aquatic life with long lasting effects. long lasting harmful effects to aquatic life	<b>_</b>		
11415 May cause				
(*)	INTERNAL CLASSIFICATION BY BIG			
CLP (EU-GHS)	Classification, labelling and packagir	ng (Globally Harmo	nised System in Europe)	
DMEL	Derived Minimal Effect Level			
DNEL	Derived No Effect Level			
EC50	Effect Concentration 50 %			
ErC50	EC50 in terms of reduction of growth rate			
LC50	Lethal Concentration 50 %			
LD50	Lethal Dose 50 %			
NOAEL NOEC	No Observed Adverse Effect Level No Observed Effect Concentration			
OECD	Organisation for Economic Co-opera	ation and Dovelon	mont	
PBT	Persistent, Bioaccumulative & Toxic		nent	
PNEC	Predicted No Effect Concentration			
STP	Sludge Treatment Process			
vPvB	very Persistent & very Bioaccumula	tive		
M-factor	- <b>,</b>			
alkanes, C14-17, c		100	Acute	BIG
alkanes, C14-17, c	nloro	10	Chronic (NRD)	BIG
Specific concentration	limits CLP			
-				
e				17.00.00
on for revision: 2.2			Publication date: 20	
			Data of rovision: 20	17 17 17

Date of revision: 2017-12-17 Product number: 58439

alkanes, C14-17, chloro	1,0 % ≤ C ≤ 20 %	EUH066	FEICA Position Paper
	,		on the classification
			and labelling of One
			Component Foam
			(OCF) containing Mid
			Chained Chlorinated
			Paraffin (MCCP) Ma
			7th 2014)
	1,0 % ≤ C ≤ 20 %	Lact. ; H362	FEICA Position Pape
			on the classification
			and labelling of One
			Component Foam
			(OCF) containing Mi
			Chained Chlorinated
			Paraffin (MCCP) Ma
			7th 2014)
	0,25 % ≤ C ≤ 20 %	Aquatic Chron. 4;H413	FEICA Position Pape
			on the classification
			and labelling of One
			Component Foam
			(OCF) containing M
			Chained Chlorinate
			Paraffin (MCCP) Ma
			7th 2014)
polymethylene polyphenyl isocyanate	C≥5 %	Eye Irrit 2;H319	analogous to Annex
	C≥5%	Skin Irrit 2;H315	analogous to Annex
	C≥0.1 %	Resp Sens 1;H334	analogous to Annex
	C≥5%	STOT SE 3;H335	analogous to Annex

The information in this safety data sheet is based on data and samples provided to BIG. The sheet was written to the best of our ability and according to the state of knowledge at that time. The safety data sheet only constitutes a guideline for the safe handling, use, consumption, storage, transport and disposal of the substances/preparations/mixtures mentioned under point 1. New safety data sheets are written from time to time. Only the most recent versions may be used. Old versions must be destroyed. Unless indicated otherwise word for word on the safety data sheet, the information does not apply to substances/preparations/mixtures in purer form, mixed with other substances or in processes. The safety data sheet offers no quality specification for the substances/preparations/mixtures in question. Compliance with the instructions in this safety data sheet does not release the user from the obligation to take all measures dictated by common sense, regulations and recommendations or which are necessary and/or useful based on the real applicable circumstances. BIG does not guarantee the accuracy or exhaustiveness of the information provided and cannot be held liable for any changes by third parties. This safety data sheet has been elaborated for use within the European Union, Switzerland, Iceland, Norway and Lichtenstein. It may be consulted in other countries, where local legislation with regards to the set-up of safety data sheets will take precedence. It is your obligation to verify and apply such local legislation. Use of this safety data sheet is subject to the licence and liability limiting conditions as stated in your BIG licence agreement or when this is failing the general conditions of BIG. All intellectual property rights to this sheet are the property of BIG and its distribution and reproduction are limited. Consult the mentioned agreement/conditions for details.

Reason for revision: 2.2

Publication date: 2017-06-02 Date of revision: 2017-12-17

Revision number: 0003