

GISS HT NOIR MAT - 879867

SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : GISS HT NOIR MAT
Product code : 879867.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Silicone alkyd resin paint for professional use

1.3. Details of the supplier of the safety data sheet

Registered company name : RUBIX Engineering.
Address : 31, Rue de la Baume.75008.PARIS.France.
Telephone : 01.44.86.08.10. Fax : .
infoclient@giss.fr
www.giss.fr
Département Sécurité Produit

1.4. Emergency telephone number : +33 (0)1 45 42 59 59.

Association/Organisation : INRS / ORFILA <http://www.centres-antipoison.net>.

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Flammable liquid, Category 3 (Flam. Liq. 3, H226).
Skin irritation, Category 2 (Skin Irrit. 2, H315).
Eye irritation, Category 2 (Eye Irrit. 2, H319).
May produce an allergic reaction (EUH208).
Specific target organ toxicity (single exposure), Category 3 (STOT SE 3, H335).
Specific target organ toxicity (repeated exposure), Category 2 (STOT RE 2, H373).
Hazardous to the aquatic environment - Chronic hazard, Category 3 (Aquatic Chronic 3, H412).

2.2. Label elements

Mixture for spray application.

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



GHS02



GHS07



GHS08

Signal Word :

WARNING

Product identifiers :

EC 215-535-7 XYLENE
EC 918-668-5 HYDROCARBONS, C9, AROMATICS
EC 202-849-4 STABILISEUR

Additional labeling :

EUH208 Contains FATTY ACIDS, TALL-OIL, ESTERS WITH POLYETHYLENE GLYCOL MONO(HYDROGEN MALEATE), COMPS. WITH AMIDES FROM DIETHYLENETRIAMINE AND TALL-OIL FATTY ACIDS. May produce an allergic reaction.

Hazard statements :

H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.

GISS HT NOIR MAT - 879867

H373	May cause damage to organs through prolonged or repeated exposure (if inhaled).
H412	Harmful to aquatic life with long lasting effects.
Precautionary statements - Prevention :	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
Precautionary statements - Response :	
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) $\geq 0.1\%$ published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Composition :

Identification	(EC) 1272/2008	Note	%
INDEX: UN0122 CAS: 7727-43-7 EC: 231-784-4 REACH: 01-2119491274-35-0001 SULFATE DE BARYUM NATUREL		[1]	10 \leq x % < 25
INDEX: UN0019 CAS: 1330-20-7 EC: 215-535-7 REACH: 01-2119488216-32-xxxx XYLENE	GHS07, GHS08, GHS02 Dgr Flam. Liq. 3, H226 Asp. Tox. 1, H304 Acute Tox. 4, H312 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Acute Tox. 4, H332 STOT SE 3, H335 STOT RE 2, H373	[1]	10 \leq x % < 25
INDEX: CH0090 EC: 918-668-5 REACH: 01-2119455851-35-XXXX HYDROCARBONS, C9, AROMATICS	GHS09, GHS07, GHS08, GHS02 Dgr Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H335 STOT SE 3, H336 Aquatic Chronic 2, H411 EUH:066		2.5 \leq x % < 10
INDEX: UN0330 CAS: 14807-96-6 EC: 238-877-9 TALC		[1]	2.5 \leq x % < 10
INDEX: CH0129 CAS: 100-41-4 EC: 202-849-4 STABILISEUR	GHS07, GHS08, GHS02 Dgr Flam. Liq. 2, H225 Asp. Tox. 1, H304 Acute Tox. 4, H332 STOT RE 2, H373 Aquatic Chronic 3, H412	[1]	2.5 \leq x % < 10

GISS HT NOIR MAT - 879867

INDEX: CH0131 CAS: 100-41-4 EC: 202-849-4 REACH: 01-2119489370-35-xxxx STABILISEUR	GHS07, GHS08, GHS02 Dgr Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Acute Tox. 4, H332 STOT SE 3, H335 STOT RE 2, H373	[1]	1 <= x % < 2.5
INDEX: UN0091 CAS: 7631-86-9 EC: 231-545-4 REACH: 01-2119379499-16-xxxx SILICE AMORPHE		[1]	0 <= x % < 1
INDEX: CH0089 CAS: 471-34-1 EC: 207-439-9 CARBONATE DE CALCIUM		[1]	0 <= x % < 1
INDEX: CH0414 CAS: 222716-38-3 FATTY ACIDS, TALL-OIL, ESTERS WITH POLYETHYLENE GLYCOL MONO(HYDROGEN MALEATE), COMPDS. WITH AMIDES FROM DIETHYLENETRIAMINE AND TALL-OIL FATTY ACIDS	GHS07, GHS09, GHS08 Wng Acute Tox. 4, H302 Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Irrit. 2, H319 STOT RE 2, H373 Aquatic Acute 1, H400 M Acute = 1 Aquatic Chronic 1, H410 M Chronic = 1		0 <= x % < 1
INDEX: CH0127 CAS: 1330-20-7 EC: 215-535-7 REACH: 01-2119488216-32-xxxx XYLENE	GHS07, GHS08, GHS02 Dgr Flam. Liq. 3, H226 Asp. Tox. 1, H304 Acute Tox. 4, H312 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Acute Tox. 4, H332 STOT SE 3, H335 STOT RE 2, H373 Aquatic Chronic 3, H412	[1]	0 <= x % < 1
INDEX: 601-021-00-3 CAS: 108-88-3 EC: 203-625-9 TOLUENE	GHS02, GHS08, GHS07 Dgr Flam. Liq. 2, H225 Repr. 2, H361d Asp. Tox. 1, H304 STOT RE 2, H373 Skin Irrit. 2, H315 STOT SE 3, H336	[1] [2]	0 <= x % < 1
INDEX: 603-004-00-6 CAS: 71-36-3 EC: 200-751-6 REACH: 01-2119484630-38-xxxx BUTAN-1-OL	GHS02, GHS05, GHS07 Dgr Flam. Liq. 3, H226 Acute Tox. 4, H302 STOT SE 3, H335 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H336	[1]	0 <= x % < 1
INDEX: 607-096-00-9 CAS: 108-31-6 EC: 203-571-6 MALEIC ANHYDRIDE	GHS08, GHS05, GHS07 Dgr Acute Tox. 4, H302 Skin Corr. 1B, H314 Resp. Sens. 1, H334 Skin Sens. 1, H317	[1]	0 <= x % < 1

GISS HT NOIR MAT - 879867

INDEX: CH0413 CAS: 111-40-0 EC: 203-865-4 REACH: 01-2119473793-27 3-AZAPENTANE-1,5-DIAMINE; DIETHYLENETRIAMINE	GHS06, GHS05 Dgr Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Corr. 1, H314 Skin Sens. 1, H317 Acute Tox. 2, H330 STOT SE 3, H335	[1]	0 <= x % < 1
---	--	-----	--------------

(Full text of H-phrases: see section 16)

Information on ingredients :

- [1] Substance for which maximum workplace exposure limits are available.
- [2] Carcinogenic, mutagenic or reprotoxic (CMR) substance.

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.
NEVER induce swallowing by an unconscious person.

4.1. Description of first aid measures

In the event of exposure by inhalation :

In the event of massive inhalation, remove the person exposed to fresh air. Keep warm and at rest.
If the person is unconscious, place in recovery position. Notify a doctor in all events, to ascertain whether observation and supportive hospital care will be necessary.
If breathing is irregular or has stopped, effect mouth-to-mouth resuscitation and call a doctor.
In the event of inhalation of spray mist, seek medical attention immediately, showing the packaging or label.
In the event of an allergic reaction, seek medical attention.

In the event of splashes or contact with eyes :

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.
If there is any redness, pain or visual impairment, consult an ophthalmologist.

In the event of splashes or contact with skin :

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.
Watch out for any remaining product between skin and clothing, watches, shoes, etc.
In the event of an allergic reaction, seek medical attention.
If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

In the event of swallowing :

Do not give the patient anything orally.
In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.
Keep the person exposed at rest. Do not force vomiting.
Seek medical attention immediately, showing the label.
If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5 : FIREFIGHTING MEASURES

Flammable.
Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

5.1. Extinguishing media

In the event of fire, use specifically suitable extinguishing agents. Never use water.
Keep packages near the fire cool, to prevent pressurised containers from bursting.

Suitable methods of extinction

- In the event of a fire, use :
- sprayed water or water mist
 - water with AFFF (Aqueous Film Forming Foam) additive
 - halon
 - foam
 - multipurpose ABC powder

GISS HT NOIR MAT - 879867

- BC powder
- carbon dioxide (CO₂)

Prevent the effluent of fire-fighting measures from entering drains or waterways.

Unsuitable methods of extinction

In the event of a fire, do not use :

- water
- water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO₂)

5.3. Advice for firefighters

Fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Because of the organic solvents contained in the mixture, eliminate sources of ignition and ventilate the area.

Avoid inhaling the vapors.

Avoid any contact with the skin and eyes.

If a large quantity has been spilt, evacuate all personnel and only allow intervention by trained operators equipped with safety apparatus.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

If the product contaminates waterways, rivers or drains, alert the relevant authorities in accordance with statutory procedures

Use drums to dispose of collected waste in compliance with current regulations (see section 13).

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

Remove contaminated clothing and protective equipment before entering eating areas.

Fire prevention :

Handle in well-ventilated areas.

Vapours are heavier than air. They can spread along the ground and form mixtures that are explosive with air.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Prevent the accumulation of electrostatic charges with connections to earth.

The mixture can become electrostatically charged : always earth during decanting operations. Wear antistatic shoes and clothing and floors should be electrically conductive.

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

GISS HT NOIR MAT - 879867

Prevent access by unauthorised personnel.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Never pour water into this mixture.

Do not inhale vapours.

Where the personnel must carry out work in a booth, whether for spraying or otherwise, the ventilation may be inadequate to control particles and solvent vapors in every case.

It is therefore recommended that personnel wear masks with a compressed air supply during spraying operations until the concentration of particles and solvent vapors has fallen below the exposure limits.

Avoid inhaling vapors. Carry out any industrial operation which may give rise to this in a sealed apparatus.

Provide vapor extraction at the emission source and also general ventilation of the premises.

Also provide breathing apparatus for certain short tasks of an exceptional nature and for emergency interventions.

In all cases, recover emissions at source.

Avoid skin and eye contact with this mixture.

Avoid exposure - obtain special instructions before use.

Packages which have been opened must be reclosed carefully and stored in an upright position.

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

Never open the packages under pressure.

7.2. Conditions for safe storage, including any incompatibilities

No data available.

Storage

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight.

Avoid accumulation of electrostatic charges.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

No data available.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits :

- European Union (2017/2398, 2017/164, 2009/161, 2006/15/CE, 2000/39/CE, 98/24/CE) :

CAS	VME-mg/m3 :	VME-ppm :	VLE-mg/m3 :	VLE-ppm :	Notes :
1330-20-7	221	50	442	100	Peau
100-41-4	442	100	884	200	Peau
100-41-4	442	100	884	200	Peau
1330-20-7	221	50	442	100	Peau
108-88-3	192	50	384	100	Peau

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
7727-43-7	10 mg/m3				
1330-20-7	100 ppm	150 ppm		A4; BEI	
14807-96-6	2 (E,R) mg/m3			A4	
100-41-4	20 ppm			A3; BEI	
100-41-4	20 ppm			A3; BEI	
471-34-1	10 mg/m3	-	-	-	-
1330-20-7	100 ppm	150 ppm		A4; BEI	
108-88-3	20 ppm			A4; BEI	
71-36-3	20 ppm				

GISS HT NOIR MAT - 879867

108-31-6	0,01 (IFV) mg/m ³			SEN; A4	
111-40-0	1 ppm			Skin	

- Germany - AGW (BAuA - TRGS 900, 29/01/2018) :

CAS	VME :	VME :	Excess	Notes
1330-20-7		100 ppm 440 mg/m ³		2(II)
100-41-4		20 ppm 88 mg/m ³		2(II)
100-41-4		20 ppm 88 mg/m ³		2(II)
7631-86-9		4 E mg/m ³		
1330-20-7		100 ppm 440 mg/m ³		2(II)
108-88-3		50 ppm 190 mg/m ³		4(II)
71-36-3		100 ppm 310 mg/m ³		1(I)
108-31-6		0,1 ppm 0,41 mg/m ³		1;=2=(I)

- France (INRS - ED984 :2016) :

CAS	VME-ppm :	VME-mg/m ³ :	VLE-ppm :	VLE-mg/m ³ :	Notes :	TMP No :
1330-20-7	50	221	100	442	*	4 Bis, 84, *
100-41-4	20	88.4	100	442	*	84
100-41-4	20	88.4	100	442	*	84
471-34-1	-	10	-	-	-	-
1330-20-7	50	221	100	442	*	4 Bis, 84, *
108-88-3	20	76.8	100	384	R2, *	4bis,84
71-36-3	-	-	50	150	-	84
108-31-6	-	-	-	1	ALL	66
111-40-0	1	4	-	-	AC	49.49 Bis

- Spain (Instituto Nacional de Seguridad e Higiene en el Trabajo (INSHT), 2017) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
7727-43-7	10 mg/m ³			e	
1330-20-7	50 ppm 221 mg/m ³	100 ppm 442 mg/m ³		via dermica,	
14807-96-6	2 mg/m ³			d,e	
100-41-4	100 ppm 441 mg/m ³	200 ppm 884 mg/m ³		via dermica, VLB®, VLI	
100-41-4	100 ppm 441 mg/m ³	200 ppm 884 mg/m ³		via dermica, VLB®, VLI	
471-34-1	10 mg/m ³				
1330-20-7	50 ppm 221 mg/m ³	100 ppm 442 mg/m ³		via dermica,	
108-88-3	50 ppm 192 mg/m ³	100 ppm 384 mg/m ³		via dermica, VLB®, VLI, r	
71-36-3	20 ppm 61 mg/m ³	50 ppm 154 mg/m ³			
108-31-6	0,1 ppm 0,4 mg/m ³			FIV, Sen	
111-40-0	1 ppm 4,3 mg/m ³			via dermica, Sen	

- UK / WEL (Workplace exposure limits, EH40/2005, 2011) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
7727-43-7	- ppm 4 mg/m ³	- ppm - mg/m ³			
1330-20-7	50 ppm 220 mg/m ³	100 ppm 441 mg/m ³		Sk, BMGV	
14807-96-6	- ppm 1 mg/m ³	- ppm - mg/m ³			

GISS HT NOIR MAT - 879867

100-41-4	100 ppm 441 mg/m ³	125 ppm 552 mg/m ³		Sk	
100-41-4	100 ppm 441 mg/m ³	125 ppm 552 mg/m ³		Sk	
471-34-1	10 mg/m ³	-	-	-	TI
1330-20-7	50 ppm 220 mg/m ³	100 ppm 441 mg/m ³		Sk, BMGV	
108-88-3	50 ppm 191 mg/m ³	100 ppm 384 mg/m ³		Sk	
71-36-3	- ppm - mg/m ³	50 ppm 154 mg/m ³		Sk	
108-31-6	- ppm 1 mg/m ³	- ppm 3 mg/m ³		Sen	
111-40-0	1 ppm 4,3 mg/m ³	- ppm - mg/m ³		Sk	

8.2. Exposure controls

Personal protection measures, such as personal protective equipment

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166.

In the event of high danger, protect the face with a face shield.

When spraying, wear a face shield in accordance with standard EN166.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

- Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- PVA (Polyvinyl alcohol)

Recommended properties :

- Impervious gloves in accordance with standard EN374

- Body protection

Avoid skin contact.

Wear suitable protective clothing.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

- Respiratory protection

Avoid breathing vapours.

If the ventilation is insufficient, wear appropriate breathing apparatus.

When workers are confronted with concentrations that are above occupational exposure limits, they must wear a suitable, approved, respiratory protection device.

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387 :

- A1 (Brown)

- A3 (Brown)

GISS HT NOIR MAT - 879867

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

General information :

Physical state : Viscous liquid.

Important health, safety and environmental information

pH : Not relevant.
Boiling point/boiling range : Not relevant.
Flash Point Interval : 23°C <= FP <= 55°C
Vapour pressure (50°C) : Below 110 kPa (1.10 bar).
Density : > 1
Water solubility : Insoluble.
Melting point/melting range : Not relevant.
Self-ignition temperature : Not relevant.
Decomposition point/decomposition range : Not relevant.

9.2. Other information

No data available.

SECTION 10 : STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

10.4. Conditions to avoid

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

Avoid :

- accumulation of electrostatic charges.
- heating
- heat
- flames and hot surfaces
- humidity

Protect from moisture. Reaction with water can cause an exothermic reaction.

10.5. Incompatible materials

Keep away from :

- water

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO₂)

SECTION 11 : TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Exposure to vapours from solvents in the mixture in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.

Symptoms produced will include headaches, numbness, dizziness, fatigue, muscular asthenia and, in extreme cases, loss of consciousness.

May cause irreversible damage to the skin; namely inflammation of the skin or the formation of erythema and eschar or oedema following exposure up to four hours.

Repeated or prolonged contact with the mixture may cause removal of natural oil from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

May have reversible effects on the eyes, such as eye irritation which is totally reversible by the end of observation at 21 days.

Splashes in the eyes may cause irritation and reversible damage

GISS HT NOIR MAT - 879867

Respiratory tract irritation may occur, together with symptoms such as coughing, choking and breathing difficulties.
May cause severe damage to organs in the event of repeated or prolonged exposure.

11.1.1. Substances

No toxicological data available for the substances.

11.1.2. Mixture

Respiratory or skin sensitisation :

Contains at least one sensitising substance. May cause an allergic reaction.

Monograph(s) from the IARC (International Agency for Research on Cancer) :

CAS 1330-20-7 : IARC Group 3 : The agent is not classifiable as to its carcinogenicity to humans.

SECTION 12 : ECOLOGICAL INFORMATION

Harmful to aquatic life with long lasting effects.

The product must not be allowed to run into drains or waterways.

12.1. Toxicity

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability

No data available.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

No data available.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

SECTION 14 : TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2017 - IMDG 2016 - ICAO/IATA 2017).

14.1. UN number

1263

14.2. UN proper shipping name

UN1263=PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound)

14.3. Transport hazard class(es)

- Classification :

3

14.4. Packing group

III

GISS HT NOIR MAT - 879867

14.5. Environmental hazards

-

14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	3	F1	III	3	30	5 L	163 367 650	E1	3	D/E

If Q <450l, see 2.2.3.1.5.1.

IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ
	3	-	III	5 L	F-E,S-E	163 223 367 955	E1

If Q <30l, see 2.3.2.5.

IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ
	3	-	III	355	60 L	366	220 L	A3 A72 A192	E1
	3	-	III	Y344	10 L	-	-	A3 A72 A192	E1

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available.

SECTION 15 : REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2018/669 (ATP 11)

- Container information:

No data available.

- Particular provisions :

No data available.

15.2. Chemical safety assessment

No data available.

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Wording of the phrases mentioned in section 3 :

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure .
H400	Very toxic to aquatic life.

GISS HT NOIR MAT - 879867

H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Abbreviations :

CMR: Carcinogenic, mutagenic or reprotoxic.
ADR : European agreement concerning the international carriage of dangerous goods by Road.
IMDG : International Maritime Dangerous Goods.
IATA : International Air Transport Association.
ICAO : International Civil Aviation Organisation
RID : Regulations concerning the International carriage of Dangerous goods by rail.
WGK : Wassergefährdungsklasse (Water Hazard Class).
GHS02 : Flame
GHS07 : Exclamation mark
GHS08 : Health hazard
PBT: Persistent, bioaccumulable and toxic.
vPvB : Very persistent, very bioaccumulable.
SVHC : Substances of very high concern.