

TECHNICAL DATASHEET

Update: 24/11/2017

G-PROFILE PROTECTIVE PU FOAMS

Description

The G-PROFILE made of polyurethane foam secures workplaces by signalling hazardous areas and absorbing impacts.

It permits to prevent risks for both the workers and equipment. With wide 3M[®] adhesive bands, it is easy to install and will keep in place during the whole product lifetime.

Flexible and available with different profiles, it fits with every situation.



Applications

Dedicated to secure all kind of workplaces environments in either production, conditioning or logistic: stairs, standard I-beams, storage racking, machines, garages, vehicles...

Characteristics

- Material PU foam
- Hardness 30-35 Shore A
- Length 1m (+/- 2cm)
- Color Black/yellow
 - Adhesive Double-coated acrylate-based 55236 3M[®]

Item #	EAN	Name	Profile type	Profile dimensions	Uses
868008	3660338218972	S-A	Rectangular for surfaces	Height 20mm (+/-1) Width 60mm (+/-1) 1 adhesive band 58mm (+/-1)	Ex.: walls or flat
868009	3660338218989	S-B	Round for surfaces	Ø 40mm (+/-1) Small height 32mm (+/-1) Flat width 32mm (+/-1) 1 adhesive band 31mm (+/-1)	surfaces
868010	3660338218996	C-A	Round for corners	Ø 40mm (+/-1) 2 adhesive bands 20mm (+/-1)	Ex.: 90° corners of furniture or walls
868011	3660338219009	E-A	Round for edges	Ø 40mm (+/-1) Slot 8x18mm (+/-1) 2 adhesive bands 15mm (+/-1)	Ex.: thin edges
868012	3660338219016	E-B	Bevelled square for edges	Height and width 40mm (+/-1) Slot 8x20mm (+/-1) 2 bevels height 14mm and width 5mm (+/-1) 2 adhesive bands 19mm (+/-1)	(INP-type), stairs

Instructions

- Carefully clean the surface to remove any grease, oil or dust traces
- Very good adhesion to metals, plastics and smooth surfaces in general
- In case of too tough surfaces to permit a good adhesion, it is still possible to use the G-PROFILE foams by fastening an intermediary smooth sheet (made of metal, wood or plastic)

Packaging

- Individual bag
- Carton of 20 units