SAFETY DATA SHEET

Based upon Regulation (EC) No 1907/2006, as amended by Regulation (EU) No 2015/830

GISS SILICONE NEUTRE INDUSTRIE [735940 + 735941]

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : GISS SILICONE NEUTRE INDUSTRIE [735940 + 735941]

Registration number REACH : Not applicable (mixture)

Product type REACH : Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant identified uses

Sealing compound

1.2.2 Uses advised against

No uses advised against known

1.3. Details of the supplier of the safety data sheet

Rubix Engineering 31, Rue de la Baume 75008 PARIS, France

Tel: +33 (0)1.44.86.08.10

infoclient@giss.fr

1.4. Emergency telephone number

24h/24h (Telephone advice: English, French, German, Dutch): +32 14 58 45 45 (BIG)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Not classified as dangerous according to the criteria of Regulation (EC) No 1272/2008

2.2. Label elements

Not classified as dangerous according to the criteria of Regulation (EC) No 1272/2008

Supplemental information

EUH208 Contains: 2-butanone oxime. May produce an allergic reaction.

2.3. Other hazards

No other hazards known

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name REACH Registration No	CAS No EC No	Conc. (C)	Classification according to CLP	Note	Remark
-------------------------------	-----------------	-----------	---------------------------------	------	--------

Created by: Brandweerinformatiecentrum voor gevaarlijke stoffen vzw (BIG)

Technische Schoolstraat 43 A, B-2440 Geel

http://www.big.be

© BIG vzw

Reason for revision: 8.2 Revision number: 0103 Publication date: 2014-10-01 Date of revision: 2017-03-13

Date of revision: 2017-03-13

134-15960-5

Product number: 55273 1 / 12

	96-29-7 202-496-6		Carc. 2; H351 Acute Tox. 4; H312 Eye Dam. 1; H318	(1)(2)	Reaction product
			Skin Sens. 1; H317		
hydrocarbons, C13-C23, n-alkanes, isoalkanes, cyclics, <0.03% aromatics 01-2119552497-29		1% <c<10%< td=""><td>Asp. Tox. 1; H304</td><td>(1)(10)</td><td>UVCB</td></c<10%<>	Asp. Tox. 1; H304	(1)(10)	UVCB

⁽¹⁾ For H-statements in full: see heading 16

SECTION 4: First aid measures

4.1. Description of first aid measures

General:

If you feel unwell, seek medical advice.

After inhalation:

Remove the victim into fresh air. Respiratory problems: consult a doctor/medical service.

After skin contact:

Wash immediately with lots of water. Soap may be used. Take victim to a doctor if irritation persists.

After eye contact:

Rinse with water. Take victim to an ophthalmologist if irritation persists.

After ingestion:

Rinse mouth with water. Consult a doctor/medical service if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

4.2.1 Acute symptoms

After inhalation:

No effects known.

After skin contact:

No effects known.

After eye contact:

No effects known.

After ingestion:

No effects known.

4.2.2 Delayed symptoms

No effects known.

4.3. Indication of any immediate medical attention and special treatment needed

If applicable and available it will be listed below.

SECTION 5: Firefighting measures

5.1. Extinguishing media

5.1.1 Suitable extinguishing media:

Polyvalent foam. ABC powder. Carbon dioxide.

5.1.2 Unsuitable extinguishing media:

No unsuitable extinguishing media known.

5.2. Special hazards arising from the substance or mixture

Upon combustion: formation of CO, CO2 and small quantities of nitrous vapours.

5.3. Advice for firefighters

5.3.1 Instructions:

No specific fire-fighting instructions required.

5.3.2 Special protective equipment for fire-fighters:

Gloves. Protective clothing. Heat/fire exposure: compressed air/oxygen apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

No naked flames.

6.1.1 Protective equipment for non-emergency personnel

See heading 8.2

6.1.2 Protective equipment for emergency responders

Reason for revision: 8.2 Publication date: 2014-10-01
Date of revision: 2017-03-13

Revision number: 0103 Product number: 55273 2 / 12

⁽²⁾ Substance with a Community workplace exposure limit

⁽¹⁰⁾ Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006

Gloves. Protective clothing.

Suitable protective clothing

See heading 8.2

6.2. Environmental precautions

Contain released product. Use appropriate containment to avoid environmental contamination.

6.3. Methods and material for containment and cleaning up

Scoop solid spill into closing containers. Clean contaminated surfaces with a soap solution. Wash clothing and equipment after handling.

6.4. Reference to other sections

See heading 13.

SECTION 7: Handling and storage

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

7.1. Precautions for safe handling

Keep away from naked flames/heat. Observe strict hygiene. Keep container tightly closed.

7.2. Conditions for safe storage, including any incompatibilities

7.2.1 Safe storage requirements:

Store in a dry area. Store at room temperature. Meet the legal requirements. Max. storage time: 1 year(s).

7.2.2 Keep away from:

Heat sources.

7.2.3 Suitable packaging material:

Synthetic material.

7.2.4 Non suitable packaging material:

No data available

7.3. Specific end use(s)

If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 Occupational exposure

a) Occupational exposure limit values

If limit values are applicable and available these will be listed below.

Ge	rm	ar	าง
u		u	1 7

Butanonoxim	Time-weighted average exposure limit 8 h (TRGS 900)	0.3 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	1 mg/m³

b) National biological limit values

If limit values are applicable and available these will be listed below.

8.1.2 Sampling methods

If applicable and available it will be listed below.

8.1.3 Applicable limit values when using the substance or mixture as intended

If limit values are applicable and available these will be listed below.

8.1.4 DNEL/PNEC values

DNEL/DMEL - Workers

2-butanone oxime

Effect level (DNEL/DMEL)	Туре	Value	Remark
DNEL	Long-term systemic effects inhalation	9 mg/m³	
	Long-term local effects inhalation	3.33 mg/m³	
	Long-term systemic effects dermal	1.3 mg/kg bw/day	
	Acute systemic effects dermal	2.5 mg/kg bw/day	

hydrocarbons, C13-C23, n-alkanes, isoalkanes, cyclics, <0.03% aromatics

Effect level (DNEL/DMEL)	Туре	Value	Remark
			no data available

DNEL/DMEL - General population

Reason for revision: 8.2 Publication date: 2014-10-01
Date of revision: 2017-03-13

Revision number: 0103 Product number: 55273 3 / 12

2-butanone oxime

Effect level (DNEL/DMEL)	Туре	Value	Remark
DNEL	Long-term systemic effects inhalation	2.7 mg/m ³	
	Long-term local effects inhalation	2 mg/m ³	
	Long-term systemic effects dermal	0.78 mg/kg bw/day	
	Acute systemic effects dermal	1.5 mg/kg bw/day	

hydrocarbons, C13-C23, n-alkanes, isoalkanes, cyclics, <0.03% aromatics

Effect level (DNEL/DMEL)	Туре	Value	Remark
			no data available

PNEC

2-butanone oxime

2 Satariorie Sairie		<u>. </u>
Compartments	Value	Remark
Fresh water	0.256 mg/l	
Aqua (intermittent releases)	0.118 mg/l	
STP	177 mg/l	

hydrocarbons, C13-C23, n-alkanes, isoalkanes, cyclics, <0.03% aromatics

Compartments	Value	Remark
		no data available

8.1.5 Control banding

If applicable and available it will be listed below.

8.2. Exposure controls

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

8.2.1 Appropriate engineering controls

Keep away from naked flames/heat. Carry operations in the open/under local exhaust/ventilation or with respiratory protection.

8.2.2 Individual protection measures, such as personal protective equipment

Observe strict hygiene. Keep container tightly closed. Do not eat, drink or smoke during work.

a) Respiratory protection

Respiratory protection not required in normal conditions.

b) Hand protection:

Gloves

- materials (good resistance)

Polyethylene.

c) Eye protection:

Safety glasses.

d) Skin protection:

Protective clothing.

8.2.3 Environmental exposure controls:

See headings 6.2, 6.3 and 13

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical form	Paste
Odour	Characteristic odour
Odour threshold	no data available
Colour	Variable in colour, depending on the composition
Particle size	no data available
Explosion limits	no data available
Flammability	Not easily combustible
Log Kow	Not applicable (mixture)
Dynamic viscosity	no data available
Kinematic viscosity	no data available
Melting point	no data available
Boiling point	no data available
Flash point	> 200 °C
Evaporation rate	no data available
Relative vapour density	no data available
Vapour pressure	no data available
Solubility	water ; insoluble
Relative density	1.0; 20 °C

Reason for revision: 8.2 Publication date: 2014-10-01
Date of revision: 2017-03-13

Revision number: 0103 Product number: 55273 4 / 12

Decomposition temperature	no data available
Auto-ignition temperature	no data available
Explosive properties	No chemical group associated with explosive properties
Oxidising properties	No chemical group associated with oxidising properties
рН	no data available

9.2. Other information

Surface tension	no data available
Saturation concentration	no data available
Absolute density	1000 kg/m³ ; 20 °C

SECTION 10: Stability and reactivity

10.1. Reactivity

Temperature above flashpoint: higher fire/explosion hazard.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Keep away from naked flames/heat.

10.5. Incompatible materials

No data available.

10.6. Hazardous decomposition products

Upon combustion: formation of CO, CO2 and small quantities of nitrous vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

11.1.1 Test results

Acute toxicity

GISS SILICONE NEUTRE INDUSTRIE [735940 + 735941]

No (test)data on the mixture available

2-butanone oxime

Route of exposure	Parameter	Method	Value	Exposure time		Value determination	Remark
Oral	LD50	Equivalent to OECD 401	2326 mg/kg bw		Rat (male)	Experimental value	
Dermal	LD50	Equivalent to OECD 402	> 1000 mg/kg bw		Rabbit (male/female)	Experimental value	
Inhalation (vapours)	LC50	Equivalent to OECD 403	> 4.83 mg/l air	4 h	Rat (male/female)	Experimental value	

hydrocarbons, C13-C23, n-alkanes, isoalkanes, cyclics, <0.03% aromatics

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value	Remark
						determination	
Oral	LD50	OECD 401	> 5000 mg/kg bw		Rat (male/female)	Experimental value	
Dermal	LD50	OECD 402	> 3160 mg/kg bw		Rabbit (male/female)	Experimental value	
Inhalation (aerosol)	LC50	OECD 403	> 5266 mg/m³ air	4 h	Rat (male/female)	Experimental value	

Judgement is based on the relevant ingredients

Conclusion

Not classified for acute toxicity

Corrosion/irritation

GISS SILICONE NEUTRE INDUSTRIE [735940 + 735941]

Route of exposure	Result	Method	Exposure time	Time point	 Value determination	Remark
	Not irritating	OECD 437			Experimental value	
	Not irritating				Expert judgement	

Reason for revision: 8.2 Publication date: 2014-10-01
Date of revision: 2017-03-13

Revision number: 0103 Product number: 55273 5 / 12

2-butanone oxime

Route of exposure	Result	Method	Exposure time	Time point	-	Value determination	Remark
Eye	, -	Equivalent to OECD 405		24; 72 hours	Rabbit	Experimental value	Single treatment
Skin	Slightly irritating	Other	24 h	1; 24; 48; 72 hours	Rabbit	Experimental value	

hydrocarbons, C13-C23, n-alkanes, isoalkanes, cyclics, <0.03% aromatics

Route of exposure	Result	Method	Exposure time	Time point	Species	Value	Remark
						determination	
Eye	Not irritating	OECD 405	24 h	24; 48; 72 hours	Rabbit	Experimental value	
Skin	Not irritating	OECD 404	4 h	24; 48; 72 hours	Rabbit	Experimental value	
Skin	Not irritating	Other	24 h	24; 48; 72 hours	Human	Experimental value	

Judgement is based on the relevant ingredients

Conclusion

Not classified as irritating to the skin

Not classified as irritating to the eyes

Not classified as irritating to the respiratory system

Respiratory or skin sensitisation

GISS SILICONE NEUTRE INDUSTRIE [735940 + 735941]

No (test)data on the mixture available

2-butanone oxime

Route of exposure	Result	Method		Observation time point	Species	Value determination	Remark
Skin		Equivalent to OECD 406	24 h	*	Guinea pig (female)	Experimental value	

hydrocarbons, C13-C23, n-alkanes, isoalkanes, cyclics, <0.03% aromatics

Route of exposure	Result	Method	•	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	OECD 406	24 h	24; 48 hours	Guinea pig (female)	Read-across	
Skin	Not sensitizing	Other	216 h	,	Human (male/female)	Experimental value	

Judgement is based on the relevant ingredients

Conclusion

Not classified as sensitizing for inhalation

Not classified as sensitizing for skin

Specific target organ toxicity

GISS SILICONE NEUTRE INDUSTRIE [735940 + 735941]

No (test)data on the mixture available

Reason for revision: 8.2 Publication date: 2014-10-01
Date of revision: 2017-03-13

Revision number: 0103 Product number: 55273 6 / 12

2-butanone oxime

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral	LOAEL	US EPA	40 mg/kg bw/day	General	Clinical signs; mortality; body weight; food consumption	13 weeks (5 days/week)	Rat (male/female)	Experimental value
Oral	NOAEL	US EPA	< 40 mg/kg bw/day	Blood	Change in the haemogramme/blood composition	13 weeks (5 days/week)	Rat (male/female)	Experimental value
Oral	NOEL	US EPA	125 mg/kg bw/day	Central nervous system	Behavioural disturbances	13 weeks (5 days/week)	Rat (male/female)	Experimental value
Oral	NOAEL	US EPA	312 ppm		Change in the haemogramme/ blood composition	13 week(s)	Rat (female)	Experimental value
Oral	NOAEL	US EPA	625 ppm		Change in the haemogramme/blood composition	13 week(s)	Rat (male)	Experimental value
Inhalation (vapours)	NOAEC	Equivalent to OECD 412	90 mg/m³ air		Change in the haemogramme/blood composition	4 weeks (6h/day, 5 days/week)	Rat (male/female)	Experimental value

hydrocarbons, C13-C23, n-alkanes, isoalkanes, cyclics, <0.03% aromatics

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time		Value determination
Oral	NOAEL	Equivalent to OECD 408	≥ 5000 mg/kg bw/day		No effect	(7)	Rat (male/female)	Read-across
Inhalation (vapours)	NOAEC	Equivalent to OECD 413	> 10400 mg/m³ air			13 weeks (6h/day, 5 days/week)	Rat (male/female)	Read-across

Judgement is based on the relevant ingredients

Conclusion

Not classified for subchronic toxicity

Mutagenicity (in vitro)

GISS SILICONE NEUTRE INDUSTRIE [735940 + 735941]

No (test)data on the mixture available

2-butanone oxime

Result	Method	Test substrate	Effect	Value determination
Ambiguous	•	Mouse (lymphoma L5178Y cells)		Experimental value
Negative	Equivalent to OECD 471	Bacteria (S.typhimurium)		Experimental value
Negative	Equivalent to OECD 482	Rat liver cells		Experimental value

hydrocarbons, C13-C23, n-alkanes, isoalkanes, cyclics, <0.03% aromatics

, .	variocarisons, CES CES, in anianes, isoanianes, cyclics, 10.0570 aromatics										
	Result	Method	Test substrate	Effect	Value determination						
	Negative	Equivalent to OECD 471	Bacteria (S.typhimurium)		Experimental value						

Mutagenicity (in vivo)

GISS SILICONE NEUTRE INDUSTRIE [735940 + 735941]

No (test)data on the mixture available

2-butanone oxime

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative	Other	3 day(s)		Male reproductive organ	Experimental value
Negative	Other		Rat (male/female)		Experimental value

hydrocarbons, C13-C23, n-alkanes, isoalkanes, cyclics, <0.03% aromatics

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative		8 weeks (6h/day, 5 days/week)	Mouse (male)		Read-across
Negative	Equivalent to OECD 475		Rat (male/female)		Read-across
Negative	Equivalent to OECD 474		Mouse (male/female)		Read-across

Reason for revision: 8.2 Publication date: 2014-10-01
Date of revision: 2017-03-13

Revision number: 0103 Product number: 55273 7/12

Judgement is based on the relevant ingredients

Conclusion

Not classified for mutagenic or genotoxic toxicity

Carcinogenicity

GISS SILICONE NEUTRE INDUSTRIE [735940 + 735941]

No (test)data on the mixture available

2-butanone oxime

Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	- 3	Value determination
Inhalation (vapours)	NOAEC	EPA OTS 798.3300		≥ 1 year(s) (6h/day, 5 days/week)		No carcinogenic effect		Experimental value
Inhalation (vapours)		EPA OTS 798.3300		≥ 1 year(s) (6h/day, 5 days/week)	Rat	Carcinogenicity	Liver	Experimental value

Judgement is based on the relevant ingredients

Conclusion

Not classified for carcinogenicity

Reproductive toxicity

GISS SILICONE NEUTRE INDUSTRIE [735940 + 735941]

No (test)data on the mixture available

2-butanone oxime

	Parameter	Method	Value	Exposure time	Species	Effect	- 3	Value determination
Developmental toxicity	NOAEL (F1)		600 mg/kg bw/day	10 day(s)	Rat	No effect		Experimental value
	LOAEL (P)		60 mg/kg bw/day	10 day(s)	Rat	Spleen enlargement/aff ection	- 1	Experimental value
Effects on fertility	NOAEL	US EPA	≥ 200 mg/kg/d		Rat (male/female)			Experimental value

hydrocarbons, C13-C23, n-alkanes, isoalkanes, cyclics, <0.03% aromatics

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity	NOAEL	Equivalent to OECD 414	> 1000 mg/kg bw/day	10 day(s)	Rat	No effect		Experimental value
Effects on fertility	NOAEC	Equivalent to OECD 416	≥ 1500 ppm	13 weeks (6h/day, 5 days/week)	Rat (male/female)	No effect		Read-across
	NOAEC	Equivalent to OECD 421	≥ 300 ppm	8 weeks (6h/day, 5 days/week)	Rat (male/female)	No effect		Read-across
	NOAEL	Equivalent to OECD 422	> 1000 mg/kg bw/day	6 weeks (daily)	Rat (male/female)	No effect		Read-across

Judgement is based on the relevant ingredients

Conclusion

Not classified for reprotoxic or developmental toxicity

Toxicity other effects

GISS SILICONE NEUTRE INDUSTRIE [735940 + 735941]

No (test)data on the mixture available

Chronic effects from short and long-term exposure

GISS SILICONE NEUTRE INDUSTRIE [735940 + 735941]

ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: Skin rash/inflammation.

SECTION 12: Ecological information

12.1. Toxicity

GISS SILICONE NEUTRE INDUSTRIE [735940 + 735941]

No (test)data on the mixture available

Reason for revision: 8.2 Publication date: 2014-10-01

Date of revision: 2017-03-13

Revision number: 0103 Product number: 55273 8 / 12

		oxime	

	Parameter	Method	Value	Duration	Species		Fresh/salt water	Value determination
Acute toxicity fishes	LC50	OECD 203	> 100 mg/l	96 h		Semi-static system	Fresh water	Experimental value; GLP
Acute toxicity crustacea	EC50	OECD 202	201 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; GLP
Toxicity algae and other aquatic plants	EC50	OECD 201	11.8 mg/l	72 h	Selenastrum capricornutum	Static system	Fresh water	Experimental value; GLP
	NOEC	OECD 201	2.56 mg/l	72 h	Selenastrum capricornutum	Static system	Fresh water	Experimental value; GLP
Long-term toxicity fish	NOEC	OECD 204	≥ 100 mg/l	14 day(s)	' '	Flow-through system	Fresh water	Experimental value; GLP
Long-term toxicity aquatic crustacea	NOEC	OECD 211	≥ 100 mg/l	21 day(s)		Semi-static system	Fresh water	Experimental value; GLP

hydrocarbons, C13-C23, n-alkanes, isoalkanes, cyclics, <0.03% aromatics

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	OECD 203	> 1028 mg/l	96 h	Scophthalmus maximus			Experimental value
Acute toxicity crustacea	LC50	Other	> 3193 mg/l	48 h	Acartia tonsa			Experimental value
Toxicity algae and other aquatic plants	ErC50	ISO 10253	> 10000 mg/l	72 h	Skeletonema costatum			Experimental value
Long-term toxicity fish	NOEL		> 1000 mg/l	28 day(s)	Oncorhynchus mykiss			QSAR
Long-term toxicity aquatic crustacea	NOEL		> 1000 mg/l	21 day(s)	Daphnia magna			QSAR
Toxicity aquatic micro- organisms	EC50	OECD 209	> 100 mg/l	3 h	Activated sludge	Static system	Fresh water	Experimental value

Judgement of the mixture is based on the relevant ingredients

Conclusion

Not classified as dangerous for the environment according to the criteria of Regulation (EC) No 1272/2008

12.2. Persistence and degradability

hydrocarbons, C13-C23, n-alkanes, isoalkanes, cyclics, <0.03% aromatics

Biodegradation water

	Method	Value	Duration	Value determination				
	OECD 306: Biodegradability in Seawater	74 %	28 day(s)	Experimental value				
ы	Newtonian control (DTC) control							

Phototransformation water (DT50 water)

No effect	Method	Value	Conc. OH-radicals	Value determination
		No effect		

Half-life soil (t1/2 soil)

Method	Value	Primary degradation/mineralisation	Value determination
	No effect		

Conclusion

Contains readily biodegradable component(s)

12.3. Bioaccumulative potential

GISS SILICONE NEUTRE INDUSTRIE [735940 + 735941]

Log Kow

Method	Remark	Value	Temperature	Value determination
	Not applicable (mixture)			

2-butanone oxime

BCF fishes

Parameter	Method	Value	Duration	Species	Value determination
BCF	OECD 305	0.5 - 5.8; GLP	A / dav/cl	Cyprinus carpio	Experimental value

Log Kow

Method	Remark	Value	Temperature	Value determination
OECD 117		0.63		Experimental value

Reason for revision: 8.2 Publication date: 2014-10-01
Date of revision: 2017-03-13

Revision number: 0103 Product number: 55273 9 / 12

hydrocarbons, C13-C23, n-alkanes, isoalkanes, cyclics, <0.03% aromatics

Log Kow

Method	Remark	Value	Temperature	Value determination
	no data available			

Conclusion

Does not contain bioaccumulative component(s)

12.4. Mobility in soil

2-butanone oxime

(log) Koc

Parameter	Method	Value	Value determination
log Koc		0.55	QSAR

hydrocarbons, C13-C23, n-alkanes, isoalkanes, cyclics, <0.03% aromatics

Percent distribution

Method	Fraction air	Fraction sediment	Fraction soil	Fraction water	Value determination
Mackay level III	8.3 %	83.2 %	7.4 %	1%	Calculated value

Contains component(s) with potential for mobility in the soil

Contains component(s) that adsorb(s) into the soil

12.5. Results of PBT and vPvB assessment

Due to insufficient data no statement can be made whether the component(s) fulfil(s) the criteria of PBT and vPvB according to Annex XIII of Regulation (EC) No 1907/2006.

12.6. Other adverse effects

GISS SILICONE NEUTRE INDUSTRIE [735940 + 735941]

Fluorinated greenhouse gases (Regulation (EU) No 517/2014)

None of the known components is included in the list of fluorinated greenhouse gases (Regulation (EU) No 517/2014)

Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009)

2-butanone oxime

Ground water

Ground water pollutant

SECTION 13: Disposal considerations

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

13.1. Waste treatment methods

13.1.1 Provisions relating to waste

European Union

Can be considered as non hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014.

Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC).

08 04 10 (wastes from MFSU of adhesives and sealants (including waterproofing products): waste adhesives and sealants other than those mentioned in 08 04 09). Depending on branch of industry and production process, also other waste codes may be applicable.

13.1.2 Disposal methods

Dissolve or mix with a combustible solvent. Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber with energy recovery. Remove waste in accordance with local and/or national regulations. Do not discharge into drains or the environment.

13.1.3 Packaging/Container

European Union

Waste material code packaging (Directive 2008/98/EC).

15 01 02 (plastic packaging).

SECTION 14: Transport information

Road (ADR), Rail (RID), Inland waterways (ADN), Sea (IMDG/IMSBC), Air (ICAO-TI/IATA-DGR)

14.1. UN number

	Transport	Not subject
14.2	2. UN proper shipping name	

14.3. Transport hazard class(es)

Hazard identification number	
Class	

Reason for revision: 8.2 Publication date: 2014-10-01 Date of revision: 2017-03-13

Revision number: 0103 Product number: 55273 10 / 12

Classification code	1
14.4. Packing group	
Packing group	
Labels	
14.5. Environmental hazards	
Environmentally hazardous substance mark	no
14.6. Special precautions for user	
Special provisions	
Limited quantities	
14.7. Transport in bulk according to Annex II of Marpol and the IBC Code	
Annex II of MARPOL 73/78	

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European legislation:

VOC content Directive 2010/75/EU

VOC content	Remark
<1%	
< 10 g/l	

REACH Annex XVII - Restriction

Contains component(s) subject to restrictions of Annex XVII of Regulation (EC) No 1907/2006: restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.

	_
· 2-butanone oxime	
· hydrocarbons, C13-C23, n-alkar	nes,
isoalkanes, cyclics, <0.03% arom	atic

Liquid substances or mixtures which are regarded as dangerous in accordance with Directive 1999/45/EC or are fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008:

- (a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F:
- b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10:
- (c) hazard class 4.1;
- (d) hazard class 5.1.

- 1. Shall not be used in:
- regarded as dangerous in accordance with ornamental articles intended to produce light or colour effects by means of different Directive 1999/45/EC or are fulfilling the criterial phases, for example in ornamental lamps and ashtrays,
 - tricks and jokes,

 — games for one or more participants, or any article intended to be used as such, even with ornamental aspects, 2. Articles not complying with paragraph 1 shall not be placed on the market. 3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they:

- can be used as fuel in decorative oil lamps for supply to the general public, and,
 present an aspiration hazard and are labelled with R65 or H304,4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN).5. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of dangerous substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met:
- a) lamp oils, labelled with R65 or H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil — or even sucking the wick of lamps — may lead to life- threatening lung damage";
- b) grill lighter fluids, labelled with R65 or H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: "Just a sip of grill lighter may lead to life threatening lung damage";
- c) lamp oils and grill lighters, labelled with R65 or H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.6. No later than 1 June 2014, the Commission shall request the European Chemicals Agency to prepare a dossier, in accordance with Article 69 of the present Regulation with a view to ban, if appropriate, grill lighter fluids and fuel for decorative lamps, labelled R65 or H304, intended for supply to the general public.7. Natural or legal persons placing on the market for the first time lamp oils and grill lighter fluids, labelled with R65 or H304, shall by 1 December 2011, and annually thereafter, provide data on alternatives to lamp oils and grill lighter fluids labelled R65 or H304 to the competent authority in the Member State concerned. Member States shall make those data available to the Commission.'

National legislation Belgium

GISS SILICONE NEUTRE INDUSTRIE [735940 + 735941]
No data available

National legislation The Netherlands

<u>GISS SILICONE NEUTRE INDUSTRIE [735940 + 735941]</u> No data available

National legislation France

GISS SILICONE NEUTRE INDUSTRIE [735940 + 735941]
No data available

National legislation Germany

GISS SILICONE NEUTRE INDUSTRIE [735940 + 735941]

Reason for revision: 8.2 Publication date: 2014-10-01
Date of revision: 2017-03-13

Revision number: 0103 Product number: 55273 11/12

WGK	1; Classification water polluting based on the components in compliance with Verwaltungsvorschrift wassergefährdender Stoffe (VwVwS) of 27 July 2005 (Anhang 4)
2-butanone oxime	
TA-Luft	5.2.5; I
TRGS900 - Risiko der Fruchtschädigung	Butanonoxim; Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes nicht befürchtet zu werden
Sensibilisierende Stoffe	Butanonoxim; Sh; Hautsensibilisierende Stoffe
Hautresorptive Stoffe	Butanonoxim; H; Hautresorptiv

National legislation United Kingdom

GISS SILICONE NEUTRE INDUSTRIE [735940 + 735941]

No data available

Other relevant data

GISS SILICONE NEUTRE INDUSTRIE [735940 + 735941]

No data available

15.2. Chemical safety assessment

No chemical safety assessment has been conducted for the mixture.

SECTION 16: Other information

Full text of any H-statements referred to under headings 2 and 3:

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H351 Suspected of causing cancer.

(*) INTERNAL CLASSIFICATION BY BIG

CLP (EU-GHS) Classification, labelling and packaging (Globally Harmonised System in Europe)

DMEL Derived Minimal Effect Level
DNEL Derived No Effect Level
EC50 Effect Concentration 50 %

ErC50 EC50 in terms of reduction of growth rate

LC50 Lethal Concentration 50 %

LD50 Lethal Dose 50 %

NOAEL No Observed Adverse Effect Level
NOEC No Observed Effect Concentration

OECD Organisation for Economic Co-operation and Development

PBT Persistent, Bioaccumulative & Toxic
PNEC Predicted No Effect Concentration

STP Sludge Treatment Process

vPvB very Persistent & very Bioaccumulative

The information in this safety data sheet is based on data and samples provided to BIG. The sheet was written to the best of our ability and according to the state of knowledge at that time. The safety data sheet only constitutes a guideline for the safe handling, use, consumption, storage, transport and disposal of the substances/preparations/mixtures mentioned under point 1. New safety data sheets are written from time to time. Only the most recent versions may be used. Old versions must be destroyed. Unless indicated otherwise word for word on the safety data sheet, the information does not apply to substances/preparations/mixtures in purer form, mixed with other substances or in processes. The safety data sheet offers no quality specification for the substances/preparations/mixtures in question. Compliance with the instructions in this safety data sheet does not release the user from the obligation to take all measures dictated by common sense, regulations and recommendations or which are necessary and/or useful based on the real applicable circumstances. BIG does not guarantee the accuracy or exhaustiveness of the information provided and cannot be held liable for any changes by third parties. This safety data sheet has been elaborated for use within the European Union, Switzerland, Iceland, Norway and Lichtenstein. It may be consulted in other countries, where local legislation with regards to the set-up of safety data sheets will take precedence. It is your obligation to verify and apply such local legislation. Use of this safety data sheet is subject to the licence and liability limiting conditions as stated in your BIG licence agreement or when this is failing the general conditions of BIG. All intellectual property rights to this sheet are the property of BIG and its distribution and reproduction are limited. Consult the mentioned agreement/conditions for details.

Reason for revision: 8.2 Publication date: 2014-10-01

Date of revision: 2017-03-13

Revision number: 0103 Product number: 55273 12 / 12