Date: 21/09/2020 Page 1/11

Revision: N°5 (16/09/2020)

SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name: GISS APPRET ANTIROUILLE GRIS

Product code: 879870.

UFI: C8S2-K08A-X00A-YMP9

1.2. Relevant identified uses of the substance or mixture and uses advised against

Alkyd reserved for professionals

1.3. Details of the supplier of the safety data sheet

Registered company name: RUBIX Engineering. Address: 31, Rue de la Baume.75008.PARIS.France.

Telephone: 01.44.86.08.10. Fax:.

infoclient@giss.fr www.giss.fr

Département Sécurité Produit

1.4. Emergency telephone number: +33 (0)1 45 42 59 59.

Association/Organisation: INRS / ORFILA http://www.centres-antipoison.net.

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Flammable liquid, Category 3 (Flam. Liq. 3, H226).

Repeated exposure may cause skin dryness or cracking (EUH066).

May produce an allergic reaction (EUH208).

Specific target organ toxicity (single exposure), Category 3 (STOT SE 3, H336).

Hazardous to the aquatic environment - Chronic hazard, Category 3 (Aquatic Chronic 3, H412).

2.2. Label elements

Mixture for spray application.

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms:





GHS02 GHS07

Signal Word : WARNING

Product identifiers:

EC 919-857-5 HYDROCARBONES, C9-C11, N-ALKANES, ISOALKANES, CYCLIQUES,<2% AROMATIQUES

EC 918-668-5 HYDROCARBONS, C9, AROMATICS

Additional labeling:

EUH208 Contains 2-BUTANONE OXIME. May produce an allergic reaction.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

 $Hazard\ statements:$

H226 Flammable liquid and vapour.
H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements - Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

Date: 21/09/2020 Page 2/11

Revision: N°5 (16/09/2020)

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/ ...

Precautionary statements - Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or

shower].

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER/doctor/... if you feel unwell.

Precautionary statements - Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Precautionary statements - Disposal:

P501 Discard the contents and container in accordance with regulations

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) >= 0.1% published by the European CHemicals Agency (ECHA) under article 57 of REACH: http://echa.europa.eu/fr/candidate-list-table

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Composition:

Composition:			
Identification	(EC) 1272/2008	Note	%
INDEX: UN0334		[1]	$25 \le x \% < 50$
CAS: 1317-65-3			
EC: 215-279-6			
CARBONATE DE CALCIUM NATUREL			
(GCC)			
INDEX: UN0122		[1]	10 <= x % < 25
CAS: 7727-43-7			
EC: 231-784-4			
REACH: 01-2119491274-35-0001			
SULFATE DE BARYUM NATUREL			
INDEX: NP0004	GHS07, GHS08, GHS02		10 <= x % < 25
CAS: 64742-48-9	Dgr		
EC: 919-857-5	Flam. Liq. 3, H226		
REACH: 01-2119463258-33	Asp. Tox. 1, H304		
	STOT SE 3, H336		
HYDROCARBONES, C9-C11, N-ALKANES,	EUH:066		
ISOALKANES, CYCLIQUES,<2%			
AROMATIQUES			
INDEX: CH0090	GHS09, GHS07, GHS08, GHS02		10 <= x % < 25
CAS: 64742-95-6	Dgr		
EC: 918-668-5	Flam. Liq. 3, H226		
REACH: 01-2119455851-35	Asp. Tox. 1, H304		
	STOT SE 3, H335		
HYDROCARBONS, C9, AROMATICS	STOT SE 3, H336		
,,	Aquatic Chronic 2, H411		
	EUH:066		
INDEX: 022-006-00-2	GHS08	[1]	2.5 <= x % < 10
CAS: 13463-67-7	Wng	[10]	
EC: 236-675-5	Carc. 2, H351	[4]	
	,		
TITANIUM DIOXIDE [IN POWDER FORM			
CONTAINING 1 % OR MORE OF PARTICLE	S		
WITH AERODYNAMIC DIAMETER <= 10			
µM]			
L7	1		

Date: 21/09/2020 Page 3/11

Revision: N°5 (16/09/2020)

INDEX: UN0330		[1]	$1 \le x \% < 2.5$
CAS: 14807-96-6			
EC: 238-877-9			
TALC			
INDEX: CH0208		[1]	1 <= x % < 2.5
CAS: 7631-86-9			
EC: 231-545-4			
REACH: 01-2119379499-16-xxxx			
SILICE AMORPHE			
INDEX: UN0043		[1]	0 <= x % < 1
CAS: 1333-86-4			
EC: 215-609-9			
REACH: 01-2119384822-32-0032			
NOIR 7			
INDEX: 616-014-00-0	GHS08, GHS05, GHS07	[1]	0 <= x % < 1
CAS: 96-29-7	Dgr		
EC: 202-496-6	Carc. 2, H351	[-]	
REACH: 01-2119539477-28-xxxx	Acute Tox. 4, H312		
	Eye Dam. 1, H318		
2-BUTANONE OXIME	Skin Sens. 1, H317		
INDEX: CH0089	5 5	[1]	0 <= x % < 1
CAS: 471-34-1		[-1	
EC: 207-439-9			
Be. 201 139 9			
CARBONATE DE CALCIUM			
INDEX: UN0004	GHS08	[1]	$0 \le x \% < 1$
CAS: 14808-60-7	Wng		
EC: 238-878-4	STOT RE 2, H373		
QUARTZ			
INDEX: CH0134	GHS07, GHS02	[1]	$0 \le x \% < 1$
CAS: 64-17-5	Dgr		
EC: 200-578-6	Flam. Liq. 2, H225		
REACH: 01-2119457610-43-0035	Eye Irrit. 2, H319		
ETHANOL			
INDEX: UN0156		[1]	$0 \le x \% < 1$
CAS: 34590-94-8			
EC: 252-104-2			
REACH: 01-2119450011-60-xxxx			
ETHER			
DIPROPYLENEGLYCOMETHYLIQUE			
INDEX: 607-009-00-4	GHS08, GHS05, GHS07	[1]	$0 \le x \% < 1$
CAS: 85-44-9	Dgr		
EC: 201-607-5	Acute Tox. 4, H302		
	STOT SE 3, H335		
PHTHALIC ANHYDRIDE	Skin Irrit. 2, H315		
	Eye Dam. 1, H318		
	Resp. Sens. 1, H334		
	Skin Sens. 1, H317		
			· · · · · · · · · · · · · · · · · · ·

(Full text of H-phrases: see section 16)

Information on ingredients:

- [1] Substance for which maximum workplace exposure limits are available.
- [2] Carcinogenic, mutagenic or reprotoxic (CMR) substance.

Note 10: The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter = $10 \mu m$.

Date: 21/09/2020 Page 4/11

Revision: N°5 (16/09/2020)

SECTION 4: FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. Description of first aid measures

In the event of exposure by inhalation:

In the event of massive inhalation, remove the person exposed to fresh air. Keep warm and at rest.

If the person is unconscious, place in recovery position. Notify a doctor in all events, to ascertain whether observation and supportive hospital care will be necessary.

If breathing is irregular or has stopped, effect mouth-to-mouth resuscitation and call a doctor.

In the event of inhalation of spray mist, seek medical attention immediately, showing the packaging or label.

In the event of an allergic reaction, seek medical attention.

In the event of splashes or contact with eyes:

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

In the event of splashes or contact with skin:

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

In the event of an allergic reaction, seek medical attention.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

In the event of swallowing:

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5: FIREFIGHTING MEASURES

Flammable.

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

5.1. Extinguishing media

In the event of fire, use specifically suitable extinguishing agents. Never use water.

Keep packages near the fire cool, to prevent pressurised containers from bursting.

Suitable methods of extinction

In the event of a fire, use:

- sprayed water or water mist
- water with AFFF (Aqueous Film Forming Foam) additive
- halon
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO2)

Prevent the effluent of fire-fighting measures from entering drains or waterways.

Unsuitable methods of extinction

In the event of a fire, do not use:

- water
- water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed:

- carbon monoxide (CO)
- carbon dioxide (CO2)

Date: 21/09/2020 Page 5/11

Revision: N°5 (16/09/2020)

5.3. Advice for firefighters

Fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Because of the organic solvents contained in the mixture, eliminate sources of ignition and ventilate the area.

Avoid inhaling the vapors.

Avoid any contact with the skin and eyes.

If a large quantity has been spilt, evacuate all personnel and only allow intervention by trained operators equipped with safety apparatus.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

If the product contaminates waterways, rivers or drains, alert the relevant authorities in accordance with statutory procedures

Use drums to dispose of collected waste in compliance with current regulations (see section 13).

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

SECTION 7: HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

Remove contaminated clothing and protective equipment before entering eating areas.

Fire prevention:

Handle in well-ventilated areas.

Vapours are heavier than air. They can spread along the ground and form mixtures that are explosive with air.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Prevent the accumulation of electrostatic charges with connections to earth.

The mixture can become electrostatically charged: always earth during decanting operations. Wear antistatic shoes and clothing and floors should be electrically non-conductive.

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

Recommended equipment and procedures:

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Never pour water into this mixture.

Avoid inhaling vapors.

Where the personnel must carry out work in a booth, whether for spraying or otherwise, the ventilation may be inadequate to control particles and solvent vapors in every case.

It is therefore recommended that personnel wear masks with a compressed air supply during spraying operations until the concentration of particles and solvent vapors has fallen below the exposure limits.

Avoid inhaling vapors. Carry out any industrial operation which may give rise to this in a sealed apparatus.

Provide vapor extraction at the emission source and also general ventilation of the premises.

Also provide breathing apparatus for certain short tasks of an exceptional nature and for emergency interventions.

Date: 21/09/2020 Page 6/11

Revision: N°5 (16/09/2020)

In all cases, recover emissions at source.

Packages which have been opened must be reclosed carefully and stored in an upright position.

Prohibited equipment and procedures:

No smoking, eating or drinking in areas where the mixture is used.

Never open the packages under pressure.

7.2. Conditions for safe storage, including any incompatibilities

No data available.

Storage

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight.

Avoid accumulation of electrostatic charges.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

No data available.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits:

- European Union (2019/1831, 2017/2398, 2017/164, 2009/161, 2006/15/CE, 2000/39/CE, 98/24/CE):

CAS	VME-mg/m3:	VME-ppm:	VLE-mg/m3:	VLE-ppm:	Notes:
34590-94-8	308	50	-	-	Peau

- France (INRS - ED984 / 2019-1487):

CAS	VME-ppm:	VME-mg/m3:	VLE-ppm:	VLE-mg/m3:	Notes:	TMP No:
1317-65-3	-	10	-	-	-	-
13463-67-7	-	10	-	-	-	-
1333-86-4	-	3.5	-	-	-	-
471-34-1	-	10	-	-	-	-
14808-60-7	-	0.1 A	-	-	-	25
64-17-5	1000	1900	5000	9500	-	84
34590-94-8	50	308	-	-	*	84
85-44-9	-	-	-	6	ALL	66.66 Bis

- UK / WEL (Workplace exposure limits, EH40/2005, 2011) :

CAS	TWA:	STEL:	Ceiling:	Definition:	Criteria:
1317-65-3	- ppm 4 mg/m³	- ppm - mg/m³			
7727-43-7	- ppm 4 mg/m³	- ppm - mg/m³			
13463-67-7	- ppm 4 mg/m³	- ppm - mg/m³			
14807-96-6	- ppm 1 mg/m³	- ppm - mg/m³			
1333-86-4	- ppm 3.5 mg/m ³	- ppm 7 mg/m³			
471-34-1	10 mg/m3	-	-	-	TI
14808-60-7	0.3 mg/m3	-	-	-	R
64-17-5	1000 ppm 1920 mg/m ³	- ppm - mg/m³			
34590-94-8	50 ppm 308 mg/m ³	- ppm - mg/m³		Sk	
85-44-9	- ppm 4 mg/m³	- ppm 12 mg/m³		Sen	

⁻ ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010):

Version: N°1 (16/09/2020) RUBIX Engineering

GISS APPRET ANTIROUILLE GRIS - 879870

Date: 21/09/2020 Page 7/11

Revision: N°5 (16/09/2020)

CAS	TWA:	STEL:	Ceiling:	Definition:	Criteria:
7727-43-7	10 mg/m3				
13463-67-7	10 mg/m3			A4	
14807-96-6	2 (E.R) mg/m3			A4	
1333-86-4	3 (I) mg/m3			A3	
471-34-1	10 mg/m3	-	-	-	-
14808-60-7	0.05 mg/m3	-	-	-	R
64-17-5		1000 ppm		A3	
34590-94-8	100 ppm	150 ppm		Skin	
85-44-9	1 ppm			SEN; A4	

- Germany - AGW (BAuA - TRGS 900, 08/08/2019) :

CAS	VME:	VME :	Excess	Notes
7631-86-9		4 mg/m ³		
96-29-7		0.3 ppm		8 (I)
		1 mg/m ³		
64-17-5		200 ppm		4(ÎTMÎTM)
		380 mg/m ³		
34590-94-8		50 ppm		1(Î TM)
		310 mg/m ³		

8.2. Exposure controls

Personal protection measures, such as personal protective equipment

Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles in accordance with standard EN166.

- Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question: other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended:

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))
- PVA (Polyvinyl alcohol)

Recommended properties:

- Impervious gloves in accordance with standard EN374

- Body protection

Avoid skin contact.

Wear suitable protective clothing.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

- Respiratory protection

Avoid breathing vapours.

If the ventilation is insufficient, wear appropriate breathing apparatus.

When workers are confronted with concentrations that are above occupational exposure limits, they must wear a suitable, approved, respiratory protection device.

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387:

- A1 (Brown)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

General information:

Physical state: Viscous liquid.

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)

Version: N°1 (16/09/2020) RUBIX Engineering

GISS APPRET ANTIROUILLE GRIS - 879870

Date: 21/09/2020 Page 8/11

Revision: N°5 (16/09/2020)

Important health, safety and environmental information

pH: Not relevant.
Boiling point/boiling range: Not relevant.

Flash Point Interval : $23^{\circ}\text{C} \le \text{FP} \le 55^{\circ}\text{C}$ Vapour pressure (50°C) : Below 110 kPa (1.10 bar).

Density: > 1
Water solubility: Insoluble.
Melting point/melting range: Not relevant.
Self-ignition temperature: Not relevant.
Decomposition point/decomposition range: Not relevant.

9.2. Other information

No data available.

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

10.4. Conditions to avoid

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

Avoid:

- accumulation of electrostatic charges.
- heating
- heat
- flames and hot surfaces
- humidity

Protect from moisture. Reaction with water can cause an exothermic reaction.

10.5. Incompatible materials

Keep away from:

- water

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO2)

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Exposure to vapours from solvents in the mixture in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.

Symptoms produced will include headaches, numbness, dizziness, fatigue, muscular asthenia and, in extreme cases, loss of consciousness.

Repeated or prolonged contact with the mixture may cause removal of natural oil from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

Splashes in the eyes may cause irritation and reversible damage

Narcotic effects may occur, such as drowsiness, narcosis, decreased alertness, loss of reflexes, lack of coordination or dizziness.

Effects may also occur in the form of violent headaches or nausea, judgement disorder, giddiness, irritability, fatigue or memory disturbance.

11.1.1. Substances

No toxicological data available for the substances.

11.1.2. Mixture

Respiratory or skin sensitisation:

Contains at least one sensitising substance. May cause an allergic reaction.

Version: N°1 (16/09/2020) RUBIX Engineering

GISS APPRET ANTIROUILLE GRIS - 879870

Monograph(s) from the IARC (International Agency for Research on Cancer):

CAS 64-17-5: IARC Group 1: The agent is carcinogenic to humans.

CAS 14808-60-7: IARC Group 1: The agent is carcinogenic to humans.

CAS 1333-86-4: IARC Group 2B: The agent is possibly carcinogenic to humans.

CAS 7631-86-9: IARC Group 3: The agent is not classifiable as to its carcinogenicity to humans.

CAS 13463-67-7: IARC Group 2B: The agent is possibly carcinogenic to humans.

SECTION 12: ECOLOGICAL INFORMATION

Harmful to aquatic life with long lasting effects.

The product must not be allowed to run into drains or waterways.

12.1. Toxicity

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability

12.2.1. Substances

ETHER DIPROPYLENEGLYCOMETHYLIQUE (CAS: 34590-94-8)

Biodegradability:

no degradability data is available, the substance is considered as not degrading quickly.

Date: 21/09/2020 Page 9/11

Revision: N°5 (16/09/2020)

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

No data available

SECTION 13: DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste:

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging:

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

SECTION 14: TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2019 - IMDG 2018 - ICAO/IATA 2020).

14.1. UN number

1263

14.2. UN proper shipping name

UN1263=PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound)

14.3. Transport hazard class(es)

- Classification :

3

14.4. Packing group

Ш

14.5. Environmental hazards

Date: 21/09/2020 Page 10/11 Revision: N°5 (16/09/2020)

14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ		Tunnel
	3	F1	III	3	30	5 L	163 367 650	E1	3	D/E

If Q <4501, see 2.2.3.1.5.1.

IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ	Stowage	Segregation
								Handling	
	3	-	III	5 L	F-E, S-E	163 223 367	E1	Category A	-
						955			

if Q < 450 l see IMDG 2.3.2.5.

	IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ
		3	-	III	355	60 L	366	220 L	A3 A72 A192	E1
I		3	-	III	Y344	10 L	-	-	A3 A72 A192	E1

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available.

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2020/217 (ATP 14)

- Container information:

No data available.

- Particular provisions :

No data available.

15.2. Chemical safety assessment

No data available.

SECTION 16: OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Wording of the phrases mentioned in section 3:

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

Abbreviations:

EUH066

CMR: Carcinogenic, mutagenic or reprotoxic.

UFI: Unique Formula Identifier

ADR: European agreement concerning the international carriage of dangerous goods by Road.

Repeated exposure may cause skin dryness or cracking.

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)

Version: N°1 (16/09/2020) RUBIX Engineering

GISS APPRET ANTIROUILLE GRIS - 879870

Date : 21/09/2020 Page 11/11 Revision : N°5 (16/09/2020)

IMDG: International Maritime Dangerous Goods. IATA: International Air Transport Association. ICAO: International Civil Aviation Organisation

RID: Regulations concerning the International carriage of Dangerous goods by rail.

 $WGK: Wasserge fahrdungsklasse \ (Water \ Hazard \ Class).$

GHS02: Flame

GHS07: Exclamation mark

PBT: Persistent, bioaccumulable and toxic. vPvB: Very persistent, very bioaccumulable. SVHC: Substances of very high concern.